

75 Ohm 141 Semi-rigid Coax Cable with Copper

RF Cables
Technical Data Sheet

PE-SR402-75-STRAIGHT

Configuration

- Semi-Rigid Cable
- 1 Shield(s)

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		36	GHz
Impedance		75		Ohms

Performance by Frequency Band

Description	F1	F2	F3	F4	F5	Units
Frequency	1	10	20			GHz
Attenuation, Typ	12.5	51	78			dB/100ft
	41.01	167.32	255.91			dB/100m
Input Power (CW), Max	280	60	39			Watts

Mechanical Specifications**Construction Specifications**

Description	Material and Plating	Diameter
Inner Conductor	Copper Clad Steel, Silver1	0.02 in 0.51 mm
Conductor Type	Solid	
Dielectric	PTFE	0.118 in 3 mm
First Shield	Copper	0.141 in 3.58 mm
Jacket	Tan	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm 141 Semi-rigid Coax Cable with Copper PE-SR402-75-STRAIGHT](#)

75 Ohm 141 Semi-rigid Coax Cable with Copper

RF Cables Technical Data Sheet

PE-SR402-75-STRAIGHT

Environmental Specifications

Temperature

Operating Range

-55 to +200 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

75 Ohm 141 Semi-rigid Coax Cable with Copper from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm 141 Semi-rigid Coax Cable with Copper PE-SR402-75-STRAIGHT](#)

URL: <https://www.pasternack.com/75-ohm-semi-rigid-141-semi-rigid-copper-tan-pe-sr402-75-straight-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE-SR402-75-STRAIGHT CAD Drawing

75 Ohm 141 Semi-rigid Coax Cable with Copper



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE-SR402-75-STRAIGHT

FSCM NO. 53919

2233

SIZE A

SCALE N/A

CAD FILE 073113

PE PASTERNAK®

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com