



WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper

Waveguide Couplers Technical Data Sheet

PE-W28CP002-10

The PE-W28CP002-10 is a millimeter-wave directional waveguide coupler that operates in the frequency range of 26.5 to 40 GHz (Ka Band). This Ka band component offers a nominal coupling level of 10 dB, mean coupling accuracy of ± 0.8 , coupling flatness of 1 dB, and has a maximum VSWR level of 1.2:1. The design is made of gold brass copper and incorporates a multi-hole configuration that results in typical directivity of 30 dB. Common applications for this millimeter wave component involve test setups where power reflection measurements are required that might involve power sampling and frequency monitoring with minimal signal loss to the main transmission path. This H plane coupler uses integrated WR-28 waveguide ports with UG 599/U flanges. Pasternack offers a complete family of waveguide millimeter wave directional couplers that are in-stock for same day shipment.

Features

- 10 dB Nominal Coupling Level
- H-Plane Waveguide Coupler
- 26.5 GHz to 40 GHz Frequency Range
- Body and Flanges made of Brass Copper
- Gold Waveguide
- 1.2:1 VSWR

Applications

- Test Benches
- Radar
- Satellite
- Microwave Radio
- Attenuation Measurements
- Power Measurements
- Source Leveling

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	26.5		40	GHz
Coupler				
Nominal Coupling Level		10		dB
Coupling Accuracy			± 0.8	dB
Directivity		30		dB
Insertion Loss			1	dB
Main Line VSWR			1.2:1	
Secondary Line VSWR			1.2:1	
Coupling Flatness			± 1	dB

Mechanical Specifications

Size

Length	9.62 in [244.35 mm]
Width	0.75 in [19.05 mm]
Height	1.775 in [45.09 mm]
Weight	0.29 lbs [131.54 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper PE-W28CP002-10](#)



WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper

Waveguide Couplers Technical Data Sheet

PE-W28CP002-10

Interface

Waveguide Size	WR-28
Flange Type	Square Cover
Flange Designation	UG-599/U
Flange Material and Plating	Brass Copper, Gold
Coupler Body Material and Plating	Brass Copper, Gold


Environmental Specifications

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper PE-W28CP002-10](#)



WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper

Waveguide Couplers Technical Data Sheet

PE-W28CP002-10




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper PE-W28CP002-10](#)

WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper



Waveguide Couplers Technical Data Sheet

PE-W28CP002-10



WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper PE-W28CP002-10](https://www.pasternack.com/wr-28-10db-directional-waveguide-coupler-ug-599-h-bend-pe-w28cp002-10-p.aspx)

URL: <https://www.pasternack.com/wr-28-10db-directional-waveguide-coupler-ug-599-h-bend-pe-w28cp002-10-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE-W28CP002-10 CAD Drawing

WR-28 Waveguide 10 dB Broadwall Coupler, UG-599/U Square Cover
Flange, H-Plane Coupled Port, 26.5 GHz to 40 GHz, Brass Copper



REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	PCR PE-W28CP002-10	3/29/2021	S.PONG

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

PE PASTERNAK
an INFINITI brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2	[.08]	FRACTIONS
.XX = ± .02	[.51]	± 1/32
.XXX = ± .005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305]	± .1 [25]	/ -0
12 [305] < L ≤ 60 [1524]	± .2 [51]	/ -0
60 [1524] < L ≤ 120 [3048]	± .4 [102]	/ -0
120 [3048] < L ≤ 300 [7620]	± .6 [152]	/ -0
300 [7620] < L	± .5% L	/ -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

SIZE A

CAGE CODE 53919

DRAWN BY K.DANG

ITEM NO. PE-W28CP002-10

REV A