



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008

Model Number PE15A6008 is a 2 to 8 GHz high gain limiting coaxial amplifier. The model operates with an input power range of -20 to +15 dBm and maintains a limited output of +19 dBm minimum. This amplifier offers a 40 dB flat high gain and a gain flatness of ± 2.0 dB independent of the input. This excellent technical performance is achieved through the use of hybrid MIC design and advanced GaAs PHEMT devices, and supplied the power typically from a +12V DC power supply. This connectorized limiting includes built-in voltage regulation, bias sequencing, and reverse bias protection for added reliability. The module is hermetically sealed for extreme environmental conditions.

Features

- 2 GHz to 8 GHz Frequency Range
- Wide Input Dynamic Range: -20 to +15 dBm
- Psat: 19dBm Min.
- High Small Signal Gain: 40 dB Min.
- Gain Flatness: ± 2 dB max
- Noise Figure: 5 dB maximum
- VSWR (In/Out) 2:1
- 50 Ohm Input and Output Matched
- -30 to 70°C Operating Temperature
- Unconditionally Stable
- Regulated Supply & Bias Sequencing
- Hermetically Sealed Module
- Overvoltage External Protection for Easy Repair

Applications

- Electronic Warfare
- Test & Measurements
- Military & Space
- Military Communication Systems
- Broadband Communication
- Microwave Receivers
- Instantaneous Frequency Measurement Receivers

Electrical Specifications (TA = +25°C, DC Voltage = 12Volts, DC Current = 300mA)

Description	Minimum	Typical	Maximum	Units
Frequency Range	2		8	GHz
Small Signal Gain	40			dB
Gain Flatness		± 2		dB
Input Power	-20		+15	dBm
Psat	+19			dBm
Psat Flatness			± 1	dB
Noise Figure			5	dB
Input VSWR		2:1		
Output VSWR		2:1		
Operating DC Voltage	11	12	13	Volts
Operating DC Current			300	mA
Operating Temperature Range	-30		+70	°C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008

Absolute Maximum Rating

Parameter	Rating	Units
Source Voltage	+15	Volts
RF input Power	+15	dBm
Operating Temperature (base-plate)	-30 to +70	°C
Storage Temperature	-55 to +85	°C



ESD Sensitive Material,
Transport material in
Approved ESD bags.
Handle only in approved
ESD Workstation.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at +25 °C, sea level
- ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation.
- Heat Sink Required for Proper Operation, Unit is cooled by conduction to heat sink.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008

Amplifier Power-up Precautions

- 1.) Confirm that proper ESD precautions and controls are always in place before handling any Amplifier module.
- 2.) Confirm adequate thermal management is in place to effectively dissipate heat away from the Amplifier package. The Amplifier operational baseplate temperature must be within the operational temperature range stated in the Amplifier datasheet. Depending on the design and thermal requirements, using a heatsink with cooling fan is always recommended for safe reliable operation. A heat sink without a cooling fan may also be used. Damage caused from overheating will void the warranty.
- 3.) Confirm adequate system grounding is established. The DC power supply and Amplifier must have a common ground in order to operate properly.
- 4.) Power Amplifiers may require additional DC Current when initially powered-up. Depending on the design, the input current draw could range from an additional 10% to 100% above the maximum rated DC current of the Amplifier. This varies based on product part number.
- 5.) Confirm the DC power supply, if limited, is set to allow for additional start-up current that's rated for the Power Amplifier.
- 6.) Confirm the system is designed and calibrated for 50 ohms. Any impedance mismatch may cause performance issues.
- 7.) Perform a CALIBRATION (if required) with the loads before connecting the Amplifier to the Network Analyzer to ensure proper performance.
- 8.) Use a fixed attenuator between the signal source and input port of the Amplifier to optimize the input VSWR match.
- 9.) Confirm the input power level at the input port of the amplifier does not exceed the maximum rated limit for input power (as stated in the Amplifier datasheet).
 P_{in} for Small Signal Gain = P1dB-SSG-10 dB
 P_{in} for P1dB = P1dB-SSG+1 dB
- 10.) Confirm the Network Analyzer is always connected to the Amplifier first before DC power is applied to the Amplifier.
- 11.) As long as the input and output ports of the amplifier are connected to a 50Ohm load and RF signal power is applied, the Amplifier can be powered up with DC voltage.
- 12.) Confirm the Amplifier output load is matched for a 50 Ohm impedance and will not exceed the maximum rated VSWR or Return Loss limit for the Amplifier. Exceeding the maximum rated VSWR or Return Loss limit will result in reflected signal power that could damage the Amplifier and void the warranty.
- 13.) **Power Amplifier connected to an Antenna for signal transmission** - It's strongly recommended to use a high power fixed attenuator pad or an Isolator between the output port of the Amplifier and input port to the antenna. Any reflected signal power due to impedance mismatch will likely damage the Amplifier and void the warranty.
- 14.) The attenuator or isolator used at the output port of the Amplifier must be rated to handle the output power level and operational frequency band of the amplifier.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)





40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008

Typical Performance Data





Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008





Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4%

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](#)



40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz,
Limiting Amplifier, -20 to +15 dBm Pin, SMA

TECHNICAL DATA SHEET

PE15A6008

availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA PE15A6008](https://www.pasternack.com/40-db-gain-8-ghz-limiting-amplifier-20-15-dbm-pin-sma-pe15a6008-p.aspx)

URL: <https://www.pasternack.com/40-db-gain-8-ghz-limiting-amplifier-20-15-dbm-pin-sma-pe15a6008-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE15A6008 CAD Drawing

40 dB Gain, 19 dBm Psat, 2 GHz to 8 GHz, Limiting Amplifier, -20 to +15 dBm Pin, SMA



NOTE:
HEAT SINK REQUIRED FOR PROPER OPERATION,
UNIT IS COOLED BY CONDUCTING TO HEAT SINK.

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE15A6008

PE PASTERNAK®
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 041014

SCALE N/A

SIZE A

2233