



Directional 30 dB SMA Coupler To 3 GHz Rated to 50 Watts

Couplers Technical Data Sheet

PE2242A-30

Features

- Directional Coupler
- 0.5 to 3 GHz Frequency Range
- Coupling 30 ± 1.5 dB
- Directivity > 18 dB
- VSWR < 1.3:1
- Max Power 50 Watts (CW)

Applications

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

Description

Directional couplers are indispensable components for isolating, separating and combining signals. For example, they provide a simple way of sampling microwave signals. They also can make accurate attenuator measurements since reflections are eliminated. The PE2242A-30 is a 30 dB directional coupler that operates from 0.5 to 3 GHz and can handle up to 50 Watts (CW) with 18 dB directivity minimum and 1.3:1 VSWR maximum. The package interface uses SMA female connectors, and is also REACH and RoHS compliant.

The PE2242A-30 is part of Pasternack's family of directional/dual-directional couplers that offer coupling ratios up to 50 dB with excellent performance featuring high directivity, low insertion loss and VSWR. They are available in both narrow and broad bandwidths and can be used in a wide variety of applications including signal sampling, VSWR measurements, power combining and distribution.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.5		3	GHz
Impedance		50		Ohms
Coupling		30 ± 1.5		dB
Insertion Loss			0.45	dB
Directivity	18			dB
Main Line VSWR			1.3:1	
Secondary Line VSWR			1.3:1	
Input Power (CW)			50	Watts

Electrical Specification Notes:
Values at 25°C, sea level.

Mechanical Specifications

Size

Length	4.72 in [119.89 mm]
Width/Dia.	0.4 in [10.16 mm]
Height	1.18 in [29.97 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 30 dB SMA Coupler To 3 GHz Rated to 50 Watts PE2242A-30](#)



Directional 30 dB SMA Coupler To 3 GHz Rated to 50 Watts

Couplers Technical Data Sheet

PE2242A-30

Weight	0.238 lbs [107.95 g]
Finish	Gray
Housing Material and Plating	Aluminum

Configuration

Package Type	Connectorized
Input Connector	SMA Female
Output Connector	SMA Female
Coupled Connectors	SMA Female

Environmental Specifications

Temperature

Operating Range	-30 to +85 deg C
-----------------	------------------

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Directional 30 dB SMA Coupler To 3 GHz Rated to 50 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 30 dB SMA Coupler To 3 GHz Rated to 50 Watts PE2242A-30](#)

URL: <https://www.pasternack.com/directional-30-db-sma-coupler-3-ghz-pe2242a-30-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE2242A-30 CAD Drawing

Directional 30 dB SMA Coupler To 3 GHz Rated to 50 Watts



LABEL

PE2242A-30

STANDARD TOLERANCES	
.X	±0.2
.XX	±0.1
.XXX	±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.

3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE2242A-30

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAGE CODE

53919

CAD FILE

041317

SCALE

N/A

SIZE

A

2233