



75 Ohm TNC Male to 75 Ohm TNC Male Cable
12 Inch Length Using 75 Ohm RG6 Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE35348LF-12

Configuration

- Connector 1: TNC Male
- Connector 2: TNC Male
- Cable Type: RG6

Features

- Max Frequency 1 GHz
- Shielding Effectivity > 90 dB
- 65.9% Phase Velocity
- Double Shielded
- PVC (NC) Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE35348LF-12 75 ohm TNC male to 75 ohm TNC male 12 inch cable using 75 ohm RG6 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to TNC cable assembly has a male to male gender configuration with 75 ohm flexible RG6 coax. The PE35348LF-12 TNC male to TNC male cable assembly operates to 1 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1	
Velocity of Propagation		65.9		%
RF Shielding	90			dB
Capacitance		20.6 [67.59]		pF/ft [pF/m]

Mechanical Specifications

Cable Assembly

Weight 0.14 lbs [63.5 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm TNC Male to 75 Ohm TNC Male Cable 12 Inch Length Using 75 Ohm RG6 Coax, RoHS PE35348LF-12](#)



75 Ohm TNC Male to 75 Ohm TNC Male Cable
12 Inch Length Using 75 Ohm RG6 Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE35348LF-12

Cable

Cable Type	RG6
Impedance	75 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel
Dielectric Type	PE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Copper Braid
Jacket Material	PVC (NC), Black
Jacket Diameter	0.332 in [8.43 mm]
One Time Minimum Bend Radius	3.5 in [88.9 mm]

Connectors

Description	Connector 1	Connector 2
Type	TNC Male	TNC Male
Impedance	75 Ohms	75 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30μ in. minimum	30μ in. minimum
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100μ in. minimum	100μ in. minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100μ in. minimum	100μ in. minimum

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm TNC Male to 75 Ohm TNC Male Cable 12 Inch Length Using 75 Ohm RG6 Coax, RoHS PE35348LF-12](#)



75 Ohm TNC Male to 75 Ohm TNC Male Cable
12 Inch Length Using 75 Ohm RG6 Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE35348LF-12

How to Order

Part Number Configuration:

PE35348LF

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE35348LF-12 = 12 inches long cable
PE35348LF-100cm = 100 cm long cable

75 Ohm TNC Male to 75 Ohm TNC Male Cable 12 Inch Length Using 75 Ohm RG6 Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm TNC Male to 75 Ohm TNC Male Cable 12 Inch Length Using 75 Ohm RG6 Coax, RoHS PE35348LF-12](#)


URL: <https://www.pasternack.com/tnc-male-tnc-male-rg6au-cable-assembly-pe35348lf-12-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE35348LF-12 CAD Drawing

75 Ohm TNC Male to 75 Ohm TNC Male Cable 12 Inch
Length Using 75 Ohm RG6 Coax, RoHS

Standard Lengths	
-12	12"
-24	24"
-36	36"
-48	48"
-60	60"
-XXX	Custom Length in Inches



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES (mm).
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE
PE35348LF-XX

PE PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

REV. A	FSCM NO. 53919	CAD FILE 020608	SCALE N/A	SIZE A	127
--------	----------------	-----------------	-----------	--------	-----