



TNC Male to BNC Male Cable 24 Inch
Length Using PE-C200 Coax

RF Cable Assemblies Technical Data Sheet

PE36068-24

Configuration

- Connector 1: TNC Male
- Connector 2: BNC Male
- Cable Type: PE-C200

Features

- Shielding Effectivity > 90 dB
- 83% Phase Velocity
- Double Shielded
- PE Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE36068-24 TNC male to BNC male 24 inch cable using PE-C200 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to BNC cable assembly has a male to male gender configuration with 50 ohm flexible PE-C200 coax. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		83		%
RF Shielding	90			dB
Capacitance		24.5 [80.38]		pF/ft [pF/m]
Jacket Spark			3,000	Vrms

Mechanical Specifications

Cable Assembly

Weight 0.088 lbs [39.92 g]

Cable

Cable Type PE-C200

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax PE36068-24](#)



TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax

RF Cable Assemblies Technical Data Sheet

PE36068-24

Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PE, Black
Jacket Diameter	0.195 in [4.95 mm]

Connectors

Description	Connector 1	Connector 2
Type	TNC Male	BNC Male
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	
Contact Plating Specification	30μ in. minimum	
Dielectric Type	Teflon	
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100μ in. minimum	

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax PE36068-24](#)



TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax

RF Cable Assemblies Technical Data Sheet

PE36068-24

How to Order

Part Number Configuration:

PE36068

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE36068-12 = 12 inches long cable
PE36068-100cm = 100 cm long cable

TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax PE36068-24](#)

URL: <https://www.pasternack.com/tnc-male-bnc-male-pe-c200-cable-assembly-pe36068-24-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE36068-24 CAD Drawing
TNC Male to BNC Male Cable 24 Inch Length Using PE-C200 Coax

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
B	PCR PE36068	3/29/22	SRAUTUS



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS				PASTERNAK an INFINITI® brand				P.O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com				THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1 SCALE N/A		REV B	
TOLERANCES:				PE36068											
X = ± .2 [.008] FRACTIONS															
.XX = ± .02 [.51] ± 1/32															
XXX = ± .005 [.13] ANGLES ± 1°															
CABLE LENGTH (L) TOLERANCES:															
L ≤ 12 [305] = ± .1 [25] / -0															
12 [305] < L ≤ 60 [1524] = ± .2 [51] / -0															
60 [1524] < L ≤ 120 [3048] = ± .4 [102] / -0															
120 [3048] < L ≤ 300 [7620] = ± .6 [152] / -0															
300 [7620] < L = ± .5% / -0															
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.															
SIZE A		CAGE CODE 53919		DRAWN BY HBAKKE		ITEM NO. PE36068									

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.