



SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM

RF Cable Assemblies Technical Data Sheet


PE39207/HS-100CM

Configuration

- Connector 1: SMB Plug
- Connector 2: SSMA Male
- Cable Type: RG316

Features

- Max Frequency 3 GHz
- 69% Phase Velocity
- FEP Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE39207/HS-100CM SMB plug to SSMA male 100 cm cable using RG316 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMB to SSMA cable assembly has a plug to male gender configuration with 50 ohm flexible RG316 coax. The PE39207/HS-100CM SMB plug to SSMA male cable assembly operates to 3 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM PE39207/HS-100CM](#)



SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM

RF Cable Assemblies Technical Data Sheet

PE39207/HS-100CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.5:1	
Velocity of Propagation		69		%
Operating Voltage (AC)			250	Vrms
Jacket Spark			2,000	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Typ.)	0.57	0.73	0.99	1.45	2.11	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Length* 39.37 in [100 cm]

Weight 0.045 lbs [20.41 g]

Cable

Cable Type RG316
 Impedance 50 Ohms
 Inner Conductor Type Stranded
 Inner Conductor Material and Plating Copper Clad Steel, Silver
 Dielectric Type PTFE
 Number of Shields 1
 Shield Layer 1 Silver Plated Copper Braid
 Jacket Material FEP, Tan
 Jacket Diameter 0.102 in [2.59 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM PE39207/HS-100CM](#)



SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM

RF Cable Assemblies Technical Data Sheet

PE39207/HS-100CM

Connectors

Description	Connector 1	Connector 2
Type	SMB Plug	SSMA Male
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Brass, Gold
Contact Plating Specification	30 µin minimum	50 µin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 µin minimum	100 µin minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100 µin minimum	100 µin minimum
Hex Size		1/4 inch

Environmental Specifications

Temperature

Operating Range -55 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM PE39207/HS-100CM](#)



SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM

RF Cable Assemblies Technical Data Sheet

PE39207/HS-100CM

How to Order

Part Number Configuration:

PE39207/HS

- xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE39207/HS-12 = 12 inches long cable
PE39207/HS-100cm = 100 cm long cable

SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM PE39207/HS-100CM](#)


URL: <https://www.pasternack.com/smb-plug-to-ssma-male-cable-using-rg316-with-heatshrink-pe39207-hs-100cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE39207/HS-100CM CAD Drawing

SMB Plug to SSMA Male Cable Using RG316 Coax with HeatShrink in 100CM

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	08/10/2022	AGANWANI



NOTES:

1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END 6.0" FROM END OF CONNECTOR

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		THIRD-ANGLE PROJECTION	
TOLERANCES:			
X = ± .2 [.08]		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.	
.XX = ± .02 [.51]		SHEET 1 OF 1	
.XXX = ± .005 [.13]		SCALE N/A	
ANGLES ± 1°			
CABLE LENGTH (L) TOLERANCES:			
L ≤ 12 [305] = ± 1 [25] / -0			
12 [305] < L ≤ 60 [1524] = ± 2 [51] / -0			
60 [1524] < L ≤ 120 [3048] = ± 4 [102] / -0			
120 [3048] < L ≤ 300 [7620] = ± 6 [152] / -0			
300 [7620] < L = ± 5% / -0			
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.			
SIZE A		REV A	
CAGE CODE 53919		ITEM NO. PE39207/HS	
DRAWN BY BPUCHASKI			
PASTERNAK an INFINITI® brand			
Pasternack Enterprises, Inc. P.O.Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com			

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.