



## TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS

### RF Cable Assemblies Technical Data Sheet

**PE39480-6**

#### Configuration


- Connector 1: TNC Male Right Angle
- Connector 2: TNC Male Right Angle
- Cable Type: PE-SR402FL

#### Features

- Dimensionally and electrically the same as standard, solid outer conductor semi-rigid coax
- Cable may be formed by hand and does not require special tools to bend
- May be formed more than once without damaging the outer conductor
- High RF Shielding >100 dB
- 100% Hi-Pot and Continuity Tested
- 100% VSWR tested to max frequency of assembly
- Standard and custom lengths ship the same day

#### Applications

- General Purpose
- Laboratory Use



#### Description

Pasternack's formable cable assemblies are hand formable semi-rigid replacements that are an alternative to costly preformed assemblies. The formable semi-rigid cable alternatives are dimensionally and electrically similar to their semi-rigid counterpart and have a tinned copper braid outer shield that provides excellent RF shielding. The hand formable cable assemblies from Pasternack do not require special tooling to shape or reshape the assemblies and can replace standard semi-rigid versions. The assemblies are available with or without a FEP jacket and are RoHS compliant.

#### Electrical Specifications

| Description             | Minimum | Typical    | Maximum | Units        |
|-------------------------|---------|------------|---------|--------------|
| Frequency Range         | DC      |            | 6       | GHz          |
| VSWR                    |         |            | 1.5:1   |              |
| Velocity of Propagation |         | 69.5       |         | %            |
| RF Shielding            | 100     |            |         | dB           |
| Capacitance             |         | 29 [95.14] |         | pF/ft [pF/m] |
| Operating Voltage (AC)  |         |            | 500     | Vrms         |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS PE39480-6](#)



TNC Male Right Angle to TNC Male Right Angle Semi-Flexible  
Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS

## RF Cable Assemblies Technical Data Sheet

**PE39480-6**

### Specifications by Frequency

| Description           | F1   | F2   | F3 | F4 | F5 | Units |
|-----------------------|------|------|----|----|----|-------|
| Frequency             | 1    | 5    |    |    |    | GHz   |
| Insertion Loss (Typ.) | 0.06 | 0.14 |    |    |    | dB    |

### Electrical Specification Notes:

Insertion loss does not include the loss of the connectors.

Insertion loss is estimated as  $0.05 \times \sqrt{f(\text{GHz})}$  dB per connector.

### Mechanical Specifications

#### Cable Assembly

|         |                     |
|---------|---------------------|
| Length* | 6 in [152.4 mm]     |
| Weight  | 0.092 lbs [41.73 g] |

#### Cable

|                                      |                           |
|--------------------------------------|---------------------------|
| Cable Type                           | PE-SR402FL                |
| Impedance                            | 50 Ohms                   |
| Inner Conductor Type                 | Solid                     |
| Inner Conductor Material and Plating | Copper Clad Steel, Silver |
| Dielectric Type                      | PTFE                      |
| Number of Shields                    | 1                         |
| Outer Conductor Material and Plating | Tinned Copper Braid       |
| Outer Conductor Diameter             | 0.141 in [3.58 mm]        |
| Repeated Minimum Bend Radius         | 0.75 in [19.05 mm]        |

### Connectors

| Description                       | Connector 1          | Connector 2          |
|-----------------------------------|----------------------|----------------------|
| Type                              | TNC Male Right Angle | TNC Male Right Angle |
| Impedance                         | 50 Ohms              | 50 Ohms              |
| Contact Material and Plating      | Brass, Gold          | Brass, Gold          |
| Dielectric Type                   | PTFE                 | PTFE                 |
| Body Material and Plating         | Brass, Nickel        | Brass, Nickel        |
| Coupling Nut Material and Plating | Brass, Nickel        | Brass, Nickel        |

### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS PE39480-6](#)



## TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS

### RF Cable Assemblies Technical Data Sheet

**PE39480-6**

#### Environmental Specifications

##### Temperature

Operating Range

-65 to +125 deg C

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

- Values at 25°C, sea level.

#### How to Order

Part Number Configuration:

**PE39480**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE39480-12 = 12 inches long cable  
PE39480-100cm = 100 cm long cable

TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable 6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS PE39480-6](#)

URL: <https://www.pasternack.com/tnc-male-tnc-male-pe-sr402fl-cable-assembly-pe39480-6-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE39480-6 CAD Drawing

TNC Male Right Angle to TNC Male Right Angle Semi-Flexible Cable  
6 Inch Length Using PE-SR402FL Coax, LF Solder, RoHS



STANDARD TOLERANCES

.X ±0.2  
.XX ±0.1  
.XXX ±0.05

\*STANDARD TOLERANCES APPLY  
ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623  
Phone: (949) 261-1920 | Fax: (949) 261-7451  
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE39480

FSCM NO. 53919

CAD FILE 110916

SCALE N/A

SIZE A

41742

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].