



SMA Male to SMA Male Cable 36 Inch Length Using LMR-240 Coax

TECHNICAL DATA SHEET

PE3C0052-36

SMA Male to SMA Male Cable 36 Inch Length Using LMR-240 Coax

Configuration

Connector 1	SMA Male
Connector 2	SMA Male
Cable Type	LMR-240
Impedance, Ohms	50

Mechanical Specifications

Cable Assembly

Cable Type	LMR-240
------------	---------

Temperature

Temperature Operating Range, deg C	-40 to +85
Temperature Storage Range, deg C	-70 to +85

Size

Length, in [mm]	36 [914.4]
Diameter, in [mm]	0.312 [7.92]
Weight, lbs [g]	0.026 [11.79]
Cable Color	Black
One Time Minimum Bend Radius, in [mm]	0.75 [19.05]
Repeated Minimum Bend Radius, in [mm]	2.5 [63.5]

Cable

No of Shields	2
Dielectric Type	PE (F)
Jacket Material	PE
Jacket Diameter, in [mm]	0.24 [6.1]

Connector 1

Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Phosphor Bronze, Gold
Coupling Nut Material and Plating	Brass, Gold
Hex Size, in	5/16
Torque, in-lbs [Nm]	5 [0.57]
Body Material and Plating	Brass, Gold
Dielectric Type	Teflon

Connector 2

Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Phosphor Bronze, Gold

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable 36 Inch Length Using LMR-240 Coax PE3C0052-36](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to SMA Male Cable 36 Inch
Length Using LMR-240 Coax

TECHNICAL DATA SHEET

PE3C0052-36

Coupling Nut Material and Plating
Hex Size, in
Torque, in-lbs [Nm]
Body Material and Plating
Dielectric Type

Brass, Gold
5/16
5 [0.57]
Brass, Gold
Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes:


Values at 25 °C, sea level

SMA Male to SMA Male Cable 36 Inch Length Using LMR-240 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable 36 Inch Length Using LMR-240 Coax PE3C0052-36](http://www.pasternack.com/sma-male-sma-male-lmr240-cable-assembly-pe3c0052-36-p.aspx)

URL: <http://www.pasternack.com/sma-male-sma-male-lmr240-cable-assembly-pe3c0052-36-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



How To Order			Part # Ext.		Length In Inches		Part # Ext.		Length In Centimeters	
Part Number Configuration			Examples							
PE3 zzz yy - xx uu			PE3000LF-100		12"		-25CM		25Cm	
			PE3000-100		24"		-50CM		50Cm	
00 - 99999			PE3000LF-100CM		36"		-75CM		75Cm	
LF = RoHS Compliant			PE3000-100CM		48"		-100CM		100Cm	
< Blank > = Standard					60"		-125CM		125Cm	
Note: LF applies only to RF cables					Custom Length		-xxCM		Custom Length	
PASTERNAK® Pasternack Enterprises, Inc. P.O. Box 16759 Irvine CA 92623 Phone: (949) 261-1920 Fax: (949) 261-7451 Website: www.pasternack.com E-Mail: sales@pasternack.com					DWG TITLE		PE3C0052			
					FSCM NO. 53919					
					CAD FILE		SCALE N/A		SIZE A	
					020513				2233	

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.