



SMA Male to TNC Male With Times Connectors Cable 24 Inch Length Using LMR-100 Coax

TECHNICAL DATA SHEET

PE3C0114-24

SMA Male to TNC Male With Times Connectors Cable 24 Inch Length Using LMR-100 Coax

Configuration

Connector 1	SMA Male
Connector 2	TNC Male
Cable Type	LMR-100A
Impedance, Ohms	50

Mechanical Specifications

Cable Assembly

Cable Type	LMR-100A
------------	----------

Temperature

Temperature Operating Range, deg C	-40 to +85
Temperature Storage Range, deg C	-70 to +85

Size

Length, in [mm]	24 [609.6]
Diameter, in [mm]	0.6 [15.24]
Weight, lbs [g]	0.121 [54.88]
Cable Color	Black
One Time Minimum Bend Radius, in [mm]	0.25 [6.35]
Repeated Minimum Bend Radius, in [mm]	1 [25.4]

Cable

No of Shields	2
Dielectric Type	PE
Jacket Material	PVC
Jacket Diameter, in [mm]	0.11 [2.79]

Connector 1

Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Brass, Gold
Coupling Nut Material and Plating	Stainless Steel
Body Material and Plating	Stainless Steel
Dielectric Type	Teflon

Connector 2

Type	TNC Male
Configuration	Straight
Inner Conductor Material and Plating	Beryllium Copper, Gold
Coupling Nut Material and Plating	Brass, Silver
Body Material and Plating	Brass, Silver

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to TNC Male With Times Connectors Cable 24 Inch Length Using LMR-100 Coax PE3C0114-24](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to TNC Male With Times Connectors
Cable 24 Inch Length Using LMR-100 Coax

TECHNICAL DATA SHEET

PE3C0114-24

Dielectric Type

Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes:

Values at 25 °C, sea level

SMA Male to TNC Male With Times Connectors Cable 24 Inch Length Using LMR-100 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to TNC Male With Times Connectors Cable 24 Inch Length Using LMR-100 Coax PE3C0114-24](http://www.pasternack.com/sma-male-tnc-male-lmr100-cable-assembly-pe3c0114-24-p.aspx)

URL: <http://www.pasternack.com/sma-male-tnc-male-lmr100-cable-assembly-pe3c0114-24-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE3C0114-24 CAD Drawing

SMA Male to TNC Male With Times Connectors Cable
24 Inch Length Using LMR-100 Coax



How To Order					
Part Number Configuration		Examples	Part # Ext.	Length In Inches	Length In Centimeters
PE3 zzz yy - xx uu		PE3000LF-100	-12	12"	-25CM
		PE3000-100	-24	24"	-50CM
		PE3000LF-100CM	-36	36"	-75CM
		PE3000-100CM	-48	48"	-100CM
			-60	60"	-125CM
00 - 99999			-xx	Custom Length	Custom Length
LF = RoHS Compliant					
< Blank > = Standard					
Note: LF applies only to RF cables					

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE
PE3C0114


PASTERNAK®
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

FSCM NO. 53919	CAD FILE 022613	SCALE N/A	SIZE A	2233
----------------	-----------------	-----------	--------	------