



**BNC Male to N Male Right Angle Cable  
39.3 Inch Length Using LMR-240 Coax**

**RF Cable Assemblies Technical Data Sheet**

**PE3C2275-100CM**

**Configuration**

- Connector 1: BNC Male
- Connector 2: N Male Right Angle
- Cable Type: LMR-240

**Features**

- Max Frequency 4 GHz
- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- PE Jacket


**Applications**

- General Purpose
- Laboratory Use

**Description**

Pasternack's PE3C2275-100CM BNC male to type N male right angle 39.3 inch cable using LMR-240 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to type N cable assembly has a male to male gender configuration with 50 ohm flexible LMR-240 coax. The PE3C2275-100CM BNC male to type N male cable assembly operates to 4 GHz. The right angle type N interface on the LMR-240 cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to N Male Right Angle Cable 39.3 Inch Length Using LMR-240 Coax PE3C2275-100CM](#)



**BNC Male to N Male Right Angle Cable**  
**39.3 Inch Length Using LMR-240 Coax**

**RF Cable Assemblies Technical Data Sheet**

**PE3C2275-100CM**

**Electrical Specifications**

| Description                   | Minimum | Typical      | Maximum | Units           |
|-------------------------------|---------|--------------|---------|-----------------|
| Frequency Range               | DC      |              | 4       | GHz             |
| VSWR                          |         |              | 1.45:1  |                 |
| Velocity of Propagation       |         | 84           |         | %               |
| RF Shielding                  | 90      |              |         | dB              |
| Group Delay                   |         | 1.21 [3.97]  |         | ns/ft [ns/m]    |
| Capacitance                   |         | 24.2 [79.4]  |         | pF/ft [pF/m]    |
| Inductance                    |         | 0.06 [0.2]   |         | uH/ft [uH/m]    |
| DC Resistance Inner Conductor |         | 3.2 [10.5]   |         | Ω/1000ft [Ω/Km] |
| DC Resistance Outer Conductor |         | 3.89 [12.76] |         | Ω/1000ft [Ω/Km] |
| Jacket Spark                  |         |              | 5,000   | Vrms            |

**Specifications by Frequency**

| Description           | F1   | F2   | F3  | F4   | F5   | Units |
|-----------------------|------|------|-----|------|------|-------|
| Frequency             | 0.1  | 0.25 | 0.5 | 1    | 4    | GHz   |
| Insertion Loss (Max.) | 0.36 | 0.38 | 0.4 | 0.46 | 0.78 | dB    |

**Electrical Specification Notes:**

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. Insertion Loss is estimated as 0.1 dB for the BNC connector and 0.2 dB for the N Male connector.

**Mechanical Specifications**

**Cable Assembly**

|          |                     |
|----------|---------------------|
| Length*  | 39.3 in [998.22 mm] |
| Diameter | 0.83 in [21.08 mm]  |

**Cable**

|                                      |                     |
|--------------------------------------|---------------------|
| Cable Type                           | LMR-240             |
| Impedance                            | 50 Ohms             |
| Inner Conductor Type                 | Solid               |
| Inner Conductor Material and Plating | Copper              |
| Dielectric Type                      | PE (F)              |
| Number of Shields                    | 2                   |
| Shield Layer 1                       | Aluminum Tape       |
| Shield Layer 2                       | Tinned Copper Braid |
| Jacket Material                      | PE, Black           |
| Jacket Diameter                      | 0.24 in [6.1 mm]    |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to N Male Right Angle Cable 39.3 Inch Length Using LMR-240 Coax PE3C2275-100CM](#)



BNC Male to N Male Right Angle Cable  
39.3 Inch Length Using LMR-240 Coax

**RF Cable Assemblies Technical Data Sheet**

**PE3C2275-100CM**

|                              |                        |
|------------------------------|------------------------|
| One Time Minimum Bend Radius | 0.75 in [19.05 mm]     |
| Repeated Minimum Bend Radius | 2.5 in [63.5 mm]       |
| Bending Moment               | 0.25 lbs-ft [0.34 N-m] |
| Flat Plate Crush             | 20 lbs/in [0.36 Kg/mm] |
| Tensile Strength             | 80 lbs [36.29 Kg]      |

**Connectors**

| Description                  | Connector 1   | Connector 2        |
|------------------------------|---------------|--------------------|
| Type                         | BNC Male      | N Male Right Angle |
| Impedance                    | 50 Ohms       | 50 Ohms            |
| Contact Material and Plating | Brass, Gold   | Brass, Gold        |
| Dielectric Type              | POM           | PTFE               |
| Body Material and Plating    | Brass, Nickel | Brass, Tri-Metal   |

**Environmental Specifications**

**Temperature**

|                 |                  |
|-----------------|------------------|
| Operating Range | -40 to +85 deg C |
|-----------------|------------------|

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to N Male Right Angle Cable 39.3 Inch Length Using LMR-240 Coax PE3C2275-100CM](#)



BNC Male to N Male Right Angle Cable  
39.3 Inch Length Using LMR-240 Coax

**RF Cable Assemblies Technical Data Sheet**

**PE3C2275-100CM**

**How to Order**

Part Number Configuration:

**PE3C2275**

**- xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C2275-12 = 12 inches long cable  
PE3C2275-100cm = 100 cm long cable

BNC Male to N Male Right Angle Cable 39.3 Inch Length Using LMR-240 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to N Male Right Angle Cable 39.3 Inch Length Using LMR-240 Coax PE3C2275-100CM](#)


URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C2275-100CM CAD Drawing

BNC Male to N Male Right Angle Cable 39.3 Inch Length Using LMR-240 Coax

| REVISIONS |                 |           |          |
|-----------|-----------------|-----------|----------|
| REV.      | DESCRIPTION     | DATE      | APPROVED |
| A         | INITIAL RELEASE | 8/20/2020 | SELLIS   |



|                                                                                                  |                 |
|--------------------------------------------------------------------------------------------------|-----------------|
| UNLESS OTHERWISE SPECIFIED<br>LEADING DIMENSIONS ARE INCHES<br>DIMENSIONS IN [ ] ARE MILLIMETERS |                 |
| TOLERANCES:                                                                                      |                 |
| .X = ± .2                                                                                        | [.08]           |
| .XX = ± .02                                                                                      | [.51]           |
| .XXX = ± .005                                                                                    | [.13]           |
| ANGLES ± 1°                                                                                      |                 |
| CABLE LENGTH (L) TOLERANCES:                                                                     |                 |
| L ≤ 12 [305]                                                                                     | ± .1 [25] / -0  |
| 12 [305] < L ≤ 60 [1524]                                                                         | ± .2 [51] / -0  |
| 60 [1524] < L ≤ 120 [3048]                                                                       | ± .4 [102] / -0 |
| 120 [3048] < L ≤ 300 [7620]                                                                      | ± .6 [152] / -0 |
| 300 [7620] < L                                                                                   | ± .5% L / -0    |
| ALL DIMENSIONS SHOWN<br>ARE FOR REFERENCE ONLY.                                                  |                 |

|                                                                                                                                                                                                   |          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| <b>PE PASTERNAK</b><br>an INFINITI® brand                                                                                                                                                         |          |
| Pasternack Enterprises, Inc.<br>P.O. Box 16759, Irvine, CA 92623.<br>Phone: 1.949.261.1920   1.866.727.8376<br>Fax: 1.949.261.7451<br>Website: www.pasternack.com<br>E-mail: sales@pasternack.com |          |
| SIZE                                                                                                                                                                                              | A        |
| CAGE CODE                                                                                                                                                                                         | 53919    |
| DRAWN BY                                                                                                                                                                                          | K.DANG   |
| ITEM NO.                                                                                                                                                                                          | PE3C2275 |
| REV                                                                                                                                                                                               | A        |

|                                                                                                                       |        |
|-----------------------------------------------------------------------------------------------------------------------|--------|
| THIRD-ANGLE PROJECTION                                                                                                |        |
| THE INFORMATION AND<br>DESIGN IN THIS DOCUMENT<br>IS THE PROPERTY OF<br>PASTERNAK CORPORATION<br>ALL RIGHTS RESERVED. |        |
| SHEET                                                                                                                 | 1 OF 1 |
| SCALE                                                                                                                 | N/A    |