



LC Male to LC Male Cable 96 Inch Length Using RG219 Coax

RF Cable Assemblies Technical Data Sheet

PE3C6034-96

Configuration

- Connector 1: LC Male
- Connector 2: LC Male
- Cable Type: RG219

Features

- Max Frequency 1 GHz
- PVC With Armor Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C6034-96 LC male to LC male 96 inch cable using RG219 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack LC to LC cable assembly has a male to male gender configuration with 50 ohm flexible RG219 coax. The PE3C6034-96 LC male to LC male cable assembly operates to 1 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1,000	MHz
Capacitance		30.8 [101.05]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	500	1,000	MHz
Insertion Loss (Typ.)	0.239	0.265	0.305	0.371	0.504	dB

Mechanical Specifications

Cable Assembly

Length*

96 in [243.84 cm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [LC Male to LC Male Cable 96 Inch Length Using RG219 Coax PE3C6034-96](#)



LC Male to LC Male Cable 96 Inch Length Using RG219 Coax

RF Cable Assemblies Technical Data Sheet

PE3C6034-96

Diameter 1.5 in [38.1 mm]

Cable

Cable Type	RG219
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper
Dielectric Type	PE
Number of Shields	1
Shield Layer 1	Copper Braid
Jacket Material	PVC With Armor
Jacket Diameter	0.945 in [24 mm]

Connectors

Description	Connector 1	Connector 2
Type	LC Male	LC Male
Specification	MIL-STD-348	MIL-STD-348
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Silver	Beryllium Copper, Silver
Outer Conductor Material and Plating	Phosphor Bronze, Nickel	Phosphor Bronze, Nickel
Body Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Hex Size	1 1/2 in	1 1/2 in
Torque	61 in-lbs [6.89 Nm]	61 in-lbs [6.89 Nm]

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [LC Male to LC Male Cable 96 Inch Length Using RG219 Coax PE3C6034-96](#)



LC Male to LC Male Cable 96 Inch Length Using RG219 Coax

RF Cable Assemblies Technical Data Sheet

PE3C6034-96

How to Order

Part Number Configuration:

PE3C6034

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C6034-12 = 12 inches long cable
PE3C6034-100cm = 100 cm long cable

LC Male to LC Male Cable 96 Inch Length Using RG219 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [LC Male to LC Male Cable 96 Inch Length Using RG219 Coax PE3C6034-96](https://www.pasternack.com/lc-male-lc-male-rg219-cable-assembly-pe3c6034-96-p.aspx)

URL: <https://www.pasternack.com/lc-male-lc-male-rg219-cable-assembly-pe3c6034-96-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C6034-96 CAD Drawing
LC Male to LC Male Cable 96 Inch Length Using RG219 Coax

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	02/08/19	J.GARCIA



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS			
TOLERANCES:			
X±.2	[5.08]	FRACTIONS	
.XX±.01	[.25]		±.132
.XXX±.005	[.13]	ANGLES ± 1°	
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.			
THIRD-ANGLE PROJECTION			

PASTERNAK an INFINITI brand		Pastermack Enterprises, Inc. P.O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 www.pasternack.com e-mail: sales@pasternack.com	
SIZE	CAGE	DRAWN BY	REV
A	53919	KDANG	A
		PART NUMBER	
		PE3C6034	
THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED.			
SHEET	1	OF	1
SCALE	N/A		

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.