

Mini SMP Female to MMCX Plug Right Angle Cable
150 cm Length Using PE-P047 Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet

PE3C6530/HS-150CM

Configuration

- Connector 1: Mini SMP Female
- Connector 2: MMCX Plug Right Angle
- Cable Type: PE-P047

Features

- Max Frequency 6 GHz
- Shielding Effectivity > 90 dB
- 70% Phase Velocity
- Double Shielded
- FEP Jacket


Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C6530/HS-150CM Mini SMP female to MMCX plug right angle 150 cm cable using PE-P047 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack Mini SMP to MMCX cable assembly has a female to plug gender configuration with 50 ohm flexible PE-P047 coax. The PE3C6530/HS-150CM Mini SMP female to MMCX plug cable assembly operates to 6 GHz. The right angle MMCX interface on the PE-P047 cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Mini SMP Female to MMCX Plug Right Angle Cable 150 cm Length Using PE-P047 Coax with HeatShrink PE3C6530/HS-150CM](#)



Mini SMP Female to MMCX Plug Right Angle Cable
150 cm Length Using PE-P047 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3C6530/HS-150CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.45:1	
Velocity of Propagation		70		%
RF Shielding	90			dB
Capacitance		29 [95.14]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.5	1	2.5	6		GHz
Insertion Loss (Max.)	1.53	2.02	2.1	4.68		dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. Insertion Loss is estimated as 0.1 dB for the Mini SMP connector and 0.2 dB for the MMCX connector.

Mechanical Specifications

Cable Assembly

Length*	59.05 in [149.99 cm]
Diameter	0.14 in [3.56 mm]

Cable

Cable Type	PE-P047
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	FEP
Number of Shields	2
Shield Layer 1	Silver Plated Copper Tape
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP, Blue
Jacket Diameter	0.056 in [1.42 mm]
One Time Minimum Bend Radius	0.2 in [5.08 mm]
Repeated Minimum Bend Radius	0.4 in [10.16 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Mini SMP Female to MMCX Plug Right Angle Cable 150 cm Length Using PE-P047 Coax with HeatShrink PE3C6530/HS-150CM](#)



Mini SMP Female to MMCX Plug Right Angle Cable
150 cm Length Using PE-P047 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3C6530/HS-150CM

Connectors

Description	Connector 1	Connector 2
Type	Mini SMP Female	MMCX Plug Right Angle
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Brass, Gold
Dielectric Type	PTFE	PTFE
Body Material and Plating	Beryllium Copper, Gold	Brass, Gold

Environmental Specifications

Temperature

Operating Range -55 to +155 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Mini SMP Female to MMCX Plug Right Angle Cable 150 cm Length Using PE-P047 Coax with HeatShrink PE3C6530/HS-150CM](#)



Mini SMP Female to MMCX Plug Right Angle Cable
150 cm Length Using PE-P047 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3C6530/HS-150CM

How to Order

Part Number Configuration:

PE3C6530/HS - xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C6530/HS-12 = 12 inches long cable
PE3C6530/HS-100cm = 100 cm long cable

Mini SMP Female to MMCX Plug Right Angle Cable 150 cm Length Using PE-P047 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Mini SMP Female to MMCX Plug Right Angle Cable 150 cm Length Using PE-P047 Coax with HeatShrink PE3C6530/HS-150CM](#)


URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C6530/HS-150CM CAD Drawing

Mini SMP Female to MMCX Plug Right Angle Cable 150 cm

Length Using PE-P047 Coax with HeatShrink



REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/24/2020	SELLIS

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2 [.08] FRACTIONS
.XX = ± .02 [.51] ± 1/32
.XXX = ± .005 [.13] ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5% L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

PE PASTERNAK
an INFINITI brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.

Phone: 1.949.261.1920 | 1.866.727.8376

Fax: 1.949.261.7451

Website: www.pasternack.com

E-mail: sales@pasternack.com

SIZE A CAGE CODE 53919 DRAWN BY K.DANG ITEM NO. PE3C6530/HS

THIRD-ANGLE PROJECTION



THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

REV A