




## SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax

### RF Cable Assemblies Technical Data Sheet

PE3W00169-24

#### Configuration

- Connector 1: SMA Male Right Angle
- Connector 2: TNC Female Bulkhead
- Cable Type: PE-SR402FL



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE3W00169-24 SMA male right angle to TNC female bulkhead 24 inch cable using PE-SR402FL coax is part of our full line of RF components available for same-day shipping. Pasternack's formable RF cable assemblies provide an alternative to costly pre-formed semi-rigid assemblies since they are hand formable. This Pasternack SMA to TNC cable assembly has a male to female gender configuration with 50 ohm formable PE-SR402FL coax. The right angle SMA interface on the PE-SR402FL cable allows for easier connections in tight spaces. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Mechanical Specifications

##### Cable Assembly

Length\*

24 in [609.6 mm]

##### Cable

Cable Type

PE-SR402FL

Impedance

50 Ohms

Inner Conductor Type

Solid

Inner Conductor Material and Plating

Copper, Silver

Dielectric Type

PTFE

Number of Shields

1

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax PE3W00169-24](#)



## SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax

### RF Cable Assemblies Technical Data Sheet

PE3W00169-24

Shield Layer 1

Tinned Copper Braid

One Time Minimum Bend Radius  
Repeated Minimum Bend Radius

0.315 in [8 mm]  
1.57 in [39.88 mm]

#### Connectors

Description	Connector 1	Connector 2
Type	SMA Male Right Angle	TNC Female Bulkhead
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	
Dielectric Type	PTFE	
Body Material and Plating	Brass, Gold	Brass, Nickel
Coupling Nut Material and Plating	Passivated Stainless Steel	
Hex Size	5/16 in.	
Torque	8 in-lbs [0.9 Nm]	

#### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8$ ", whichever is greater.

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax PE3W00169-24](#)



## SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax

### RF Cable Assemblies Technical Data Sheet

PE3W00169-24

#### How to Order

Part Number Configuration:

**PE3W00169**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3W00169-12 = 12 inches long cable  
PE3W00169-100cm = 100 cm long cable

SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using PE-SR402FL Coax PE3W00169-24](#)

URL: <https://www.pasternack.com/sma-male-tnc-female-pe-sr402fl-cable-assembly-pe3w00169-24-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

**PE3W00169-24 CAD Drawing**  
**SMA Male Right Angle to TNC Female Bulkhead Cable**  
**24 Inch Length Using PE-SR402FL Coax**

