



N Female Bulkhead to TNC Male Right Angle  
Cable 36 Inch Length Using LMR-240 Coax

**RF Cable Assemblies Technical Data Sheet**


**PE3W00415-36**

**Configuration**

- Connector 1: N Female Bulkhead
- Connector 2: TNC Male Right Angle
- Cable Type: LMR-240

**Features**

- Max Frequency 4 GHz
- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- PE Jacket



**Applications**

- General Purpose
- Laboratory Use

**Description**

Pasternack's PE3W00415-36 type N female bulkhead to TNC male right angle 36 inch cable using LMR-240 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to TNC cable assembly has a female to male gender configuration with 50 ohm flexible LMR-240 coax. The PE3W00415-36 type N female to TNC male cable assembly operates to 4 GHz. The right angle TNC interface on the LMR-240 cable allows for easier connections in tight spaces. Our RF cable assembly with type N bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax PE3W00415-36](#)



N Female Bulkhead to TNC Male Right Angle  
Cable 36 Inch Length Using LMR-240 Coax

**RF Cable Assemblies Technical Data Sheet**

**PE3W00415-36**

**Electrical Specifications**

| Description                   | Minimum | Typical      | Maximum | Units           |
|-------------------------------|---------|--------------|---------|-----------------|
| Frequency Range               | DC      |              | 4       | GHz             |
| VSWR                          |         |              | 1.5:1   |                 |
| Velocity of Propagation       |         | 84           |         | %               |
| RF Shielding                  | 90      |              |         | dB              |
| Group Delay                   |         | 1.21 [3.97]  |         | ns/ft [ns/m]    |
| Capacitance                   |         | 24.2 [79.4]  |         | pF/ft [pF/m]    |
| Inductance                    |         | 0.06 [0.2]   |         | uH/ft [uH/m]    |
| DC Resistance Inner Conductor |         | 3.2 [10.5]   |         | Ω/1000ft [Ω/Km] |
| DC Resistance Outer Conductor |         | 3.89 [12.76] |         | Ω/1000ft [Ω/Km] |
| Jacket Spark                  |         |              | 5,000   | Vrms            |

**Specifications by Frequency**

| Description           | F1   | F2   | F3   | F4   | F5  | Units |
|-----------------------|------|------|------|------|-----|-------|
| Frequency             | 0.1  | 0.25 | 0.5  | 1    | 4   | GHz   |
| Insertion Loss (Max.) | 0.27 | 0.32 | 0.38 | 0.45 | 0.7 | dB    |

**Electrical Specification Notes:**

The Insertion Loss data above is based on the performance specifications of the coax cable used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

**Mechanical Specifications**

**Cable Assembly**

|          |                   |
|----------|-------------------|
| Length*  | 36 in [914.4 mm]  |
| Diameter | 0.87 in [22.1 mm] |

**Cable**

|                                      |                     |
|--------------------------------------|---------------------|
| Cable Type                           | LMR-240             |
| Impedance                            | 50 Ohms             |
| Inner Conductor Type                 | Solid               |
| Inner Conductor Material and Plating | Copper              |
| Dielectric Type                      | PE (F)              |
| Number of Shields                    | 2                   |
| Shield Layer 1                       | Aluminum Tape       |
| Shield Layer 2                       | Tinned Copper Braid |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax PE3W00415-36](#)



## N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax

### RF Cable Assemblies Technical Data Sheet

**PE3W00415-36**

|                              |                        |
|------------------------------|------------------------|
| Jacket Material              | PE, Black              |
| Jacket Diameter              | 0.24 in [6.1 mm]       |
| One Time Minimum Bend Radius | 0.75 in [19.05 mm]     |
| Repeated Minimum Bend Radius | 2.5 in [63.5 mm]       |
| Bending Moment               | 0.25 lbs-ft [0.34 N-m] |
| Flat Plate Crush             | 20 lbs/in [0.36 Kg/mm] |
| Tensile Strength             | 80 lbs [36.29 Kg]      |

#### Connectors

| Description                       | Connector 1       | Connector 2          |
|-----------------------------------|-------------------|----------------------|
| Type                              | N Female Bulkhead | TNC Male Right Angle |
| Specification                     | MIL-STD-348A      |                      |
| Impedance                         | 50 Ohms           | 50 Ohms              |
| Contact Material and Plating      | Brass, Gold       | Brass, Gold          |
| Dielectric Type                   | Teflon            | Teflon               |
| Body Material and Plating         | Brass, Tri-Metal  | Brass, Nickel        |
| Coupling Nut Material and Plating |                   | Brass, Nickel        |

Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax PE3W00415-36](#)




N Female Bulkhead to TNC Male Right Angle  
Cable 36 Inch Length Using LMR-240 Coax

## RF Cable Assemblies Technical Data Sheet

**PE3W00415-36**

### Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax PE3W00415-36](#)



N Female Bulkhead to TNC Male Right Angle  
Cable 36 Inch Length Using LMR-240 Coax

**RF Cable Assemblies Technical Data Sheet**

**PE3W00415-36**

**How to Order**

Part Number Configuration:

**PE3W00415**

**- xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3W00415-12 = 12 inches long cable  
PE3W00415-100cm = 100 cm long cable

N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax PE3W00415-36](#)

URL: <https://www.pasternack.com/n-female-tnc-male-lmr240-cable-assembly-pe3w00415-36-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

### N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax

### N Female Bulkhead to TNC Male Right Angle Cable 36 Inch Length Using LMR-240 Coax



## STANDARD TOLERANCES

 $\pm 0.2$  $\pm 0.01$ 

|     |        |
|-----|--------|
| XXX | ±0.005 |
| XXX | ±0.005 |

\*STANDARD TOLERANCES APPLY  
ONLY TO DIMENSIONS IN INCHES



**PASTERNAK®**  
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

**Phone: (949) 261-1920 | Fax: (949) 261-7451**

**Website:** [www.pasternack.com](http://www.pasternack.com) | **E-Mail:** [sales@pasternack.com](mailto:sales@pasternack.com)

**DWG TITLE**

PE3W00415

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
3. DIMENSIONS ARE IN INCHES [mm].

CAGE CODE 53919

**CAD FILE** 05/09/18

SCALE N/A

**SIZE A**

CN2379