



75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable
36 Inch Length Using 75 Ohm PE-B159-RD Red Coax

RF Cable Assemblies Technical Data Sheet

PE3W01571/RD-36

Configuration

- Connector 1: RCA Male
- Connector 2: RCA Female Bulkhead
- Cable Type: MINI 59

Features

- Double Shielded
- PVC Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W01571/RD-36 75 ohm RCA male to 75 ohm RCA female bulkhead 36 inch cable using 75 ohm PE-B159-RD coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack RCA to RCA cable assembly has a male to female gender configuration with 75 ohm flexible MINI 59 coax. Our RF cable assembly with RCA bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Mechanical Specifications

Cable Assembly

Length*	36 in [914.4 mm]
Diameter	0.56 in [14.22 mm]

Cable

Cable Type	MINI 59
Impedance	75 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PVC, Red
Jacket Diameter	0.159 in [4.04 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable 36 Inch Length Using 75 Ohm PE-B159-RD Red Coax PE3W01571/RD-36](#)



75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable
36 Inch Length Using 75 Ohm PE-B159-RD Red Coax

RF Cable Assemblies Technical Data Sheet

PE3W01571/RD-36

One Time Minimum Bend Radius

1.5 in [38.1 mm]

Connectors

Description	Connector 1	Connector 2
Type	RCA Male	RCA Female Bulkhead
Impedance	75 Ohms	75 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Dielectric Type	Delrin	POM
Body Material and Plating	Brass, Gold	Brass, Nickel

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable 36 Inch Length Using 75 Ohm PE-B159-RD Red Coax PE3W01571/RD-36](#)



75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable
36 Inch Length Using 75 Ohm PE-B159-RD Red Coax

RF Cable Assemblies Technical Data Sheet

PE3W01571/RD-36

How to Order

Part Number Configuration:

PE3W01571/RD - xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W01571/RD-12 = 12 inches long cable
PE3W01571/RD-100cm = 100 cm long cable

75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable 36 Inch Length Using 75 Ohm PE-B159-RD Red Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable 36 Inch Length Using 75 Ohm PE-B159-RD Red Coax PE3W01571/RD-36](#)


URL: <https://www.pasternack.com/rca-male-rca-female-pe-b159-rd-cable-assembly-pe3w01571-rd-36-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W01571/RD-36 CAD Drawing

75 Ohm RCA Male to 75 Ohm RCA Female Bulkhead Cable
36 Inch Length Using 75 Ohm PE-B159-RD Red Coax

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/30/19	SELLIS



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS			
TOLERANCES:			
X±.2	[5.08]	FRACTIONS	
XX±.01	[.25]		±1/32
XXX±.005	[.13]	ANGLES ± 1°	
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.			
THIRD-ANGLE PROJECTION			

PE PASTERNAK an INFINITI brand			
Pasternack Enterprises, Inc. P.O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 www.pasternack.com e-mail: sales@pasternack.com			
SIZE	CAGE	DRAWN BY	PART NUMBER
A	53919	K.DANG	PE3W01571/RD
			REV
			A

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED.			
SHEET	1	OF	1
SCALE	N/A		

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT
ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.