



N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder

RF Cable Assemblies Technical Data Sheet


PE3W01964LF/HS-50CM

Configuration

- Connector 1: N Male
- Connector 2: N Male
- Cable Type: PE-P195

Features

- Max Frequency 3 GHz
- Shielding Effectivity > 90 dB
- 80% Phase Velocity
- Triple Shielded
- FEP Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W01964LF/HS-50CM type N male to type N male 50 cm cable using PE-P195 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to type N cable assembly has a male to male gender configuration with 50 ohm flexible PE-P195 coax. The PE3W01964LF/HS-50CM type N male to type N male cable assembly operates to 3 GHz. The triple shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder PE3W01964LF/HS-50CM](#)



N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W01964LF/HS-50CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.5:1	
Velocity of Propagation		80		%
RF Shielding	90			dB
Group Delay		1.27 [4.17]		ns/ft [ns/m]
Capacitance		29 [95.14]		pF/ft [pF/m]
Inductance		0.064 [0.21]		uH/ft [uH/m]
DC Resistance Inner Conductor Km]		7.6 [24.93]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor Km]		4.9 [16.08]		Ohms/1000ft [Ohms/Km]
Jacket Spark			3,000	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	3	GHz
Insertion Loss (Max.)	0.3	0.34	0.39	0.52	0.53	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. The Insertion Loss includes an estimated loss of 0.2dB of connector loss.

Mechanical Specifications

Cable Assembly

Length*	19.68 in [499.87 mm]
Diameter	0.81 in [20.57 mm]

Cable

Cable Type	PE-P195
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	3
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Aluminum Tape

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder PE3W01964LF/HS-50CM](#)



N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W01964LF/HS-50CM

Shield Layer 3
Jacket Material Silver Plated Copper Braid
Jacket Diameter FEP, Tan
0.195 in [4.95 mm]

Repeated Minimum Bend Radius 1 in [25.4 mm]

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Male
Specification	MIL-STD-348	MIL-STD-348
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	ASTM B488	ASTM B488
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Hex Size	13/16 Inch	13/16 Inch

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder PE3W01964LF/HS-50CM](#)



N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W01964LF/HS-50CM

How to Order

Part Number Configuration:

PE3W01964LF/HS - xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W01964LF/HS-12 = 12 inches long cable
PE3W01964LF/HS-100cm = 100 cm long cable

N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder PE3W01964LF/HS-50CM](#)

URL: <https://www.pasternack.com/n-male-n-male-pe-p195-cable-assembly-pe3w01964lf-hs-50cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W01964LF/HS-50CM CAD Drawing

N Male to N Male Cable 50 cm Length Using PE-P195 Coax with HeatShrink, LF Solder

