



SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet


PE3W03671LF-200CM

Configuration

- Connector 1: SMA Male Right Angle
- Connector 2: TNC Male Right Angle
- Cable Type: RG223

Features

- Max Frequency 3 GHz
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W03671LF-200CM SMA male right angle to TNC male right angle 200 cm cable using RG223 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMA to TNC cable assembly has a male to male gender configuration with 50 ohm flexible RG223 coax. The PE3W03671LF-200CM SMA male to TNC male cable assembly operates to 3 GHz. The right angle SMA and right angle TNC interfaces on the RG223 cable allow for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.5:1	
Velocity of Propagation		66		%
Capacitance		30.8 [101.05]		pF/ft [pF/m]
Operating Voltage (AC)			500	Vrms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder PE3W03671LF-200CM](#)



SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W03671LF-200CM

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	3	GHz
Insertion Loss (Max.)	0.734	0.846	1.279	1.79	2.026	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax use in this assembly. The Insertion Loss includes an estimated insertion loss of 0.4dB of connector Loss

Mechanical Specifications

Cable Assembly

Length*
Diameter

78.74 in [200 cm]
0.59 in [14.99 mm]

Cable

Cable Type
Impedance
Inner Conductor Type
Inner Conductor Material and Plating
Dielectric Type
Number of Shields
Shield Layer 1
Shield Layer 2
Jacket Material
Jacket Diameter

RG223
50 Ohms
Solid
Copper, Silver
PE
2
Silver Plated Copper Braid
Silver Plated Copper Braid
PVC, Black
0.209 in [5.31 mm]

Repeated Minimum Bend Radius

1 in [25.4 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder PE3W03671LF-200CM](#)



SMA Male Right Angle to TNC Male Right Angle Cable
200 cm Length Using RG223 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W03671LF-200CM

Connectors

Description	Connector 1	Connector 2
Type	SMA Male Right Angle	TNC Male Right Angle
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	50 μ in minimum	30 μ in minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 μ in minimum	100 μ in minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100 μ in minimum	100 μ in minimum
Hex Size	5/16 inch	
Torque	3 in-lbs [0.34 Nm]	

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8$ ", whichever is greater.

Environmental Specifications

Temperature

Operating Range

-40 to +80 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder PE3W03671LF-200CM](#)



SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W03671LF-200CM

How to Order

Part Number Configuration:

PE3W03671LF

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W03671LF-12 = 12 inches long cable
PE3W03671LF-100cm = 100 cm long cable

SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to TNC Male Right Angle Cable 200 cm Length Using RG223 Coax , LF Solder PE3W03671LF-200CM](#)

URL: <https://www.pasternack.com/sma-male-tnc-male-rg223u-cable-assembly-pe3w03671lf-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W03671LF-200CM CAD Drawing
 SMA Male Right Angle to TNC Male Right Angle Cable
 200 cm Length Using RG223 Coax , LF Solder

REVISIONS				
REV.	DESCRIPTION	DATE	APPROVED	
A	INITIAL RELEASE	04/19/19	S.SELLIS	



UNLESS OTHERWISE SPECIFIED
 LEADING DIMENSIONS ARE INCHES
 DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:	
X=± .2 [5.08]	FRACTIONS $\pm .132$
.XX=± .01 [.25]	ANGLES $\pm 1^\circ$
XXX=± .005 [.13]	

ALL DIMENSIONS SHOWN
 ARE FOR REFERENCE ONLY.
 THIRD-ANGLE PROJECTION

PASTERNAK
 an INFINITE brand

Pasternack Enterprises, Inc.
 P.O.Box 167659, Irvine, CA 92623.
 Phone: 1.949.261.1920 / 1.866.727.8376
 Fax: 1.949.261.7451
www.pasternack.com | [email: sales@pasternack.com](mailto:sales@pasternack.com)

SHEET 1 OF 1
 SCALE N/A
 PART NUMBER PE3W03671LF
 REV A

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.