

N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM



# **RF Cable Assemblies Technical Data Sheet**

# PE3W03732/SP1-100CM


# Configuration

Connector 1: N Male Right AngleConnector 2: TNC Male Right Angle

Cable Type: LMR-400

#### **Features**

- Max Frequency 5.8 GHz
- Shielding Effectivity > 90 dB
- 85% Phase Velocity
- · Double Shielded
- PE Jacket



# **Applications**

General Purpose

Laboratory Use

### Description

Pasternack's PE3W03732/SP1-100CM type N male right angle to TNC male right angle cable using LMR-400 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to TNC cable assembly has a male to male gender configuration with 50 ohm flexible LMR-400 coax. The PE3W03732/SP1-100CM type N male to TNC male cable assembly operates to 5.8 GHz. The right angle type N and right angle TNC interfaces on the LMR-400 cable allow for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM PE3W03732/SP1-100CM

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM



### **RF Cable Assemblies Technical Data Sheet**

### PE3W03732/SP1-100CM

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		5.8	GHz
VSWR		130	1.5:1	
Velocity of Propagation		85		%
RF Shielding	90			dB
Group Delay		1.2 [3.94]		ns/ft [ns/m]
Capacitance		23.9 [78.41]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor		1.39 [4.56]		Ω/1000ft [Ω/Km]
DC Resistance Outer Conductor		1.65 [5.41]	3	Ω/1000ft [Ω/Km]
Jacket Spark			8,000	Vrms

### **Specifications by Frequency**

-	- 1					
Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	6	GHz
Insertion Loss (Typ.)	0.47	0.5	0.54	0.63	0.76	dB/ft
	1.54	1.64	1.77	2.07	2.49	dB/m

**Electrical Specification Notes:** 

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.2 dB per connector.

### **Mechanical Specifications**

### Cable Assembly

Length\* 39.37 in [100 cm]
Weight 0.379 lbs [171.91 g]

#### Cable

Cable Type LMR-400 Impedance 50 Ohms Inner Conductor Type Solid

Inner Conductor Material and Plating Copper Clad Aluminum

Dielectric Type PE (F)
Number of Shields 2

Shield Layer 1 Aluminum Tape
Shield Layer 2 Tinned Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM PE3W03732/SP1-100CM

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM



# **RF Cable Assemblies Technical Data Sheet**

# PE3W03732/SP1-100CM

Jacket Material PE, Black

Jacket Diameter 0.405 in [10.29 mm]

One Time Minimum Bend Radius

1 in [25.4 mm]

Repeated Minimum Bend Radius

4 in [101.6 mm]

Bending Moment

0.5 lbs-ft [0.68 N-m]

Flat Plate Crush

40 lbs/in [0.71 Kg/mm]

Tensile Strength

160 lbs [72.57 Kg]

#### **Connectors**

Description	Connector 1	Connector 2	
Туре	N Male Right Angle	TNC Male Right Angle	
Specification	MIL-STD-348A		
Impedance	50 Ohms	50 Ohms	
Mating Cycles	500		
Contact Material and Plating	Brass, Gold	Brass, Silver	
Contact Plating Specification	30 μin minimum		
Dielectric Type	PTFE	PTFE	
Body Material and Plating	Brass, Tri-Metal	Brass, Silver	
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Silver	

### **Environmental Specifications**

**Temperature** 

Operating Range -40 to +85 deg C

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM PE3W03732/SP1-100CM

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM



# **RF Cable Assemblies Technical Data Sheet**

# PE3W03732/SP1-100CM

#### How to Order



Example: PE3W03732/SP1-12 = 12 inches long cable PE3W03732/SP1-100cm = 100 cm long cable

N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM PE3W03732/SP1-100CM

URL: https://www.pasternack.com/n-male-right-angle-to-tnc-male-cable-using-lmr-400-with-heatshrink-and-180-deg.-clockpe3w03732-sp1-100CM-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

# PE3W03732/SP1-100CM CAD Drawing

N Male Right Angle to TNC Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink and 90 Deg. Clock in 100CM

