

# SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax



# RF Cable Assemblies Technical Data Sheet

PE3W04442-60

# Configuration

• Connector 1: SMA Male

• Connector 2: SMA Male Right Angle

Cable Type: RG188

#### **Features**

• Max Frequency 400 MHz

PTFE Jacket

# **Applications**

· General Purpose

Laboratory Use

#### Description

Pasternack's PE3W04442-60 SMA male to SMA male right angle 60 inch cable using RG188 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMA to SMA cable assembly has a male to male gender configuration with 50 ohm flexible RG188 coax. The PE3W04442-60 SMA male to SMA male cable assembly operates to 400 MHz. The right angle SMA interface on the RG188 cable allows for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		400	MHz
VSWR			1.4:1	

# Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	400					MHz
Insertion Loss (Max.)	1.3					dB

**Electrical Specification Notes:** 

The Insertion Loss data above is based on the performance specifications of the coax use in this assembly. The Insertion Loss includes an estimated insertion loss of 0.3dB of connector Loss

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax PE3W04442-60

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax



# RF Cable Assemblies Technical Data Sheet

PE3W04442-60

# **Mechanical Specifications**

**Cable Assembly** 

 Length\*
 60 in [152.4 cm]

 Diameter
 0.315 in [8 mm]

Cable

Cable Type Impedance

Inner Conductor Type

Inner Conductor Material and Plating

Dielectric Type Number of Shields Shield Layer 1

Jacket Material
Jacket Diameter

RG188 50 Ohms Stranded

Copper Clad Steel, Silver

PTFE

1

Silver Plated Copper Braid

PTFE, White 0.11 in [2.79 mm]

#### **Connectors**

Description	Connector 1	Connector 2 SMA Male Right Angle	
Туре	SMA Male		
Specification	MIL-STD-348A	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms	
Contact Material and Plating	Brass, Gold	Brass, Gold	
Contact Plating Specification	30 μin minimum	50 µin minimum	
Dielectric Type	PTFE	PTFE	
Body Material and Plating	Brass, Nickel	Brass, Nickel	
Body Plating Specification	100 µin minimum	100 μin minimum	
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel	
Coupling Nut Plating Specification	100 µin minimum	100 µin minimum	
Hex Size	5/16 inch	5/16 inch	
Torque	3 in-lbs [0.34 Nm]	3 in-lbs [0.34 Nm]	

Mechanical Specification Notes:

### Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax PE3W04442-60

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

<sup>\*</sup>All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



# SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax



# RF Cable Assemblies Technical Data Sheet

PE3W04442-60

### **How to Order**



Example: PE3W04442-12 = 12 inches long cable

PE3W04442-100cm = 100 cm long cable

SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax PE3W04442-60

URL: https://www.pasternack.com/sma-male-sma-male-rg188au-cable-assembly-pe3w04442-60-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

PE3W04442-60 CAD Drawing
SMA Male to SMA Male Right Angle Cable 60 Inch Length Using RG188 Coax

