



Snap-On QN Male Right Angle to N Female
Cable 50 cm Length Using LMR-400 Coax

RF Cable Assemblies Technical Data Sheet

PE3W04619-50CM

Configuration

- Connector 1: Snap-On QN Male Right Angle
- Connector 2: N Female
- Cable Type: LMR-400

Features

- Max Frequency 5.8 GHz
- Shielding Effectivity > 90 dB
- 85% Phase Velocity
- Double Shielded
- PE Jacket


Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W04619-50CM QN male snap-on right angle to type N female 50 cm cable using LMR-400 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack QN to type N cable assembly has a male to female gender configuration with 50 ohm flexible LMR-400 coax. The PE3W04619-50CM QN male to type N female cable assembly operates to 5.8 GHz. The right angle QN interface on the LMR-400 cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Snap-On QN Male Right Angle to N Female Cable 50 cm Length Using LMR-400 Coax PE3W04619-50CM](#)



Snap-On QN Male Right Angle to N Female
Cable 50 cm Length Using LMR-400 Coax

RF Cable Assemblies Technical Data Sheet

PE3W04619-50CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		5.8	GHz
VSWR			1.5:1	
Velocity of Propagation		85		%
RF Shielding	90			dB
Group Delay		1.2 [3.94]		ns/ft [ns/m]
Capacitance		23.9 [78.41]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor Km]		1.39 [4.56]		Ohms/1000ft [Ohms/
DC Resistance Outer Conductor Km]		1.65 [5.41]		Ohms/1000ft [Ohms/
Jacket Spark			8,000	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.5	1	2	4	5.8	GHz
Insertion Loss (Max.)	0.35	0.36	0.4	0.44	0.48	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax use in this assembly. The Insertion Loss includes an estimated insertion loss of 0.3dB of connector Loss

Mechanical Specifications

Cable Assembly

Length*	19.68 in [499.87 mm]
Diameter	0.75 in [19.05 mm]

Cable

Cable Type	LMR-400
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Snap-On QN Male Right Angle to N Female Cable 50 cm Length Using LMR-400 Coax PE3W04619-50CM](#)



Snap-On QN Male Right Angle to N Female
Cable 50 cm Length Using LMR-400 Coax

RF Cable Assemblies Technical Data Sheet

PE3W04619-50CM

Jacket Material	PE, Black
Jacket Diameter	0.405 in [10.29 mm]
One Time Minimum Bend Radius	1 in [25.4 mm]
Repeated Minimum Bend Radius	4 in [101.6 mm]
Bending Moment	0.5 lbs-ft [0.68 N-m]
Flat Plate Crush	40 lbs/in [0.71 Kg/mm]
Tensile Strength	160 lbs [72.57 Kg]

Connectors

Description	Connector 1	Connector 2
Type	QN Male Right Angle	N Female
Impedance	50 Ohms	50 Ohms
Connection Method	Snap-On	
Mating Cycles	100	
Contact Material and Plating	Brass, Silver	Phosphor Bronze, Gold
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Silver	Brass, Tri-Metal
Coupling Nut Material and Plating	Brass, Tri-Metal	

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Environmental Specifications

Temperature

Operating Range -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Snap-On QN Male Right Angle to N Female Cable 50 cm Length Using LMR-400 Coax PE3W04619-50CM](#)



Snap-On QN Male Right Angle to N Female
Cable 50 cm Length Using LMR-400 Coax

RF Cable Assemblies Technical Data Sheet

PE3W04619-50CM

How to Order

Part Number Configuration:

PE3W04619

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W04619-12 = 12 inches long cable
PE3W04619-100cm = 100 cm long cable

Snap-On QN Male Right Angle to N Female Cable 50 cm Length Using LMR-400 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Snap-On QN Male Right Angle to N Female Cable 50 cm Length Using LMR-400 Coax PE3W04619-50CM](https://www.pasternack.com/qn-male-n-female-lmr400-cable-assembly-pe3w04619-50cm-p.aspx)

URL: <https://www.pasternack.com/qn-male-n-female-lmr400-cable-assembly-pe3w04619-50cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W04619-50CM CAD Drawing

Snap-On QN Male Right Angle to N Female Cable 50 cm Length Using LMR-400 Coax

