

Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax

RF Cable Assemblies Technical Data Sheet

PE3W05762

Configuration

• Connector 1: TNC Female Reverse Polarity Bulkhead

· Connector 2: SSMC Plug Right Angle

Cable Type: RG188

Features

• Max Frequency 400 MHz

PTFE Jacket

Applications

· General Purpose

· Laboratory Use

Description

Pasternack's PE3W05762 reverse polarity TNC female bulkhead to SSMC plug right angle cable using RG188 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack reverse polarity TNC to SSMC cable assembly has a female to plug gender configuration with 50 ohm flexible RG188 coax. The PE3W05762 reverse polarity TNC female to SSMC plug cable assembly operates to 400 MHz. The right angle SSMC interface on the RG188 cable allows for easier connections in tight spaces. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		400	MHz
VSWR			1.5:1	

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	400					MHz
Insertion Loss (Max.)	0.5					dB/ft
	1.64					dB/m

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax PE3W05762

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax



RF Cable Assemblies Technical Data Sheet

PE3W05762

Electrical Specification Notes:

Insertion Loss does not include the loss of connectors. Insertion Loss is estimated as 0.3dB of connector loss

Mechanical Specifications

Cable Assembly

Diameter 0.75 in [19.05 mm]

Cable

Cable TypeRG188Impedance50 OhmsInner Conductor TypeStranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE
Number of Shields 1

Shield Layer 1 Silver Plated Copper Braid

Jacket MaterialPTFE, WhiteJacket Diameter0.11 in [2.79 mm]

Connectors

Description	Connector 1	Connector 2	
Туре	TNC Female Reverse Polarity Bulkhead	SSMC Plug Right Angle	
Impedance	50 Ohms	50 Ohms	
Mating Cycles		500	
Contact Material and Plating	Phosphor Bronze, Gold	Beryllium Copper, Gold	
Contact Plating Specification	30 μin minimum	MIL-G-45204	
Dielectric Type	PTFE	Teflon	
Body Material and Plating	Brass, Nickel	Brass, Gold	
Body Plating Specification		MIL-G-45204	
Coupling Nut Material and Plating		Beryllium Copper, Gold	
Coupling Nut Plating Specification		MIL-G-45204	
Torque		1.75 in-lbs [0.2 Nm]	

Mechanical Specification Notes:

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax PE3W05762

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax



RF Cable Assemblies Technical Data Sheet

PE3W05762

How to Order



Example: PE3W05762-12 = 12 inches long cable

PE3W05762-100cm = 100 cm long cable

Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax PE3W05762

URL: https://www.pasternack.com/tnc-female-ssmc-plug-rg188au-cable-assembly-pe3w05762-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE3W05762 CAD Drawing
Reverse Polarity TNC Female Bulkhead to SSMC Plug Right Angle Cable Using RG188 Coax

