



## BMA Jack Slide-On Hermetically Sealed Thread-In Mount

### RF Connectors Technical Data Sheet

PE45354

#### Configuration

- Slide-On BMA Jack Connector
- 50 Ohms

- Straight Body Geometry
- Thread-In

#### Features

- Max. Operating Frequency 22 GHz
- Excellent VSWR of 1.25:1
- Gold Plated Beryllium Copper Contact
- 51.18 $\mu$  in. minimum contact plating

- Blind Mate Connector
- Hermetically Sealed
- IP68

#### Applications

- General Purpose Test

#### Description

Pasternack's PE45354 BMA jack slide-on thread-in mount hermetically sealed connector with none attachment is part of our full line of RF components available for same-day shipping. Our BMA jack connector operates up to a maximum frequency of 22 GHz and offers excellent VSWR of 1.25:1. The Pasternack blind mate connector is ideal for applications where direct visual or tactile access to the connection point is not possible, for example, when two circuit boards need to be mated. The connector has an IP68 rating to protect against dust and prolonged moisture protection under immersion conditions.

Our BMA jack thread-in connector PE45354 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		22	GHz
VSWR			1.25:1	
Insertion Loss		0.32		dB
Operating Voltage (AC)			500	Vrms
Dielectric Withstanding Voltage (AC)			1,500	Vrms
Insulation Resistance	5,000			MOhms

#### Mechanical Specifications

##### Size

Length  
Width/Dia.

0.47 in [11.94 mm]  
0.25 in [6.35 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BMA Jack Slide-On Hermetically Sealed Thread-In Mount PE45354](#)



## BMA Jack Slide-On Hermetically Sealed Thread-In Mount

### RF Connectors Technical Data Sheet

PE45354

Weight	0.004 lbs [1.81 g]
Mating Cycles	1,000 Cycles

#### Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold 51.18 $\mu$ in. minimum
Insulation	PTFE	
Body	Passivated Stainless Steel	
Gasket	Silicone Rubber	

#### Environmental Specifications

##### Temperature

Operating Range	-65 to +125 deg C
Ingress Protection (IP) Rating	IP68
Hermetic Seal	1E-8 atm. cm <sup>3</sup> /s (Helium)

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:


BMA Jack Slide-On Hermetically Sealed Thread-In Mount from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BMA Jack Slide-On Hermetically Sealed Thread-In Mount PE45354](#)

URL: <https://www.pasternack.com/bma-jack-slide-on-connector-pe45354-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

**PE45354 CAD Drawing**  
BMA Jack Slide-On Hermetically Sealed Thread-In Mount



**STANDARD TOLERANCES**  
 .X  $\pm 0.2$   
 .XX  $\pm 0.1$   
 .XXX  $\pm 0.05$

\*STANDARD TOLERANCES APPLY  
ONLY TO DIMENSIONS IN INCHES

**PASTERNACK**  
THE ENGINEER'S RF SOURCE



Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)

DWG TITLE	PE45354
CAGE CODE	53919

**NOTES:**  
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
 3. DIMENSIONS ARE IN INCHES [mm].



**Mounting Procedure**

1. Assemble metal gasket onto connector.
2. Tighten the connector up to 280 Ncm torque (24.78 Lbs. In)
3. Thus the connection hermeticity is guaranteed at 1 .10-5 atm.cm<sup>3</sup>/sec.  
Then solder the pin.

**Panel Drilling**

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE	PE45354
CAGE CODE	53919

<b>PASTERNAK®</b> THE ENGINEER'S RF SOURCE Pasternack Enterprises, Inc. P.O. Box 16759   Irvine   CA   92623 Phone: (949) 261-1920   Fax: (949) 261-7451 Website: <a href="http://www.pasternack.com">www.pasternack.com</a>   E-Mail: <a href="mailto:sales@pasternack.com">sales@pasternack.com</a>	CAD FILE	020917	SCALE	N/A	SIZE	A	2233
--	----------	--------	-------	-----	------	---	------