



40 dB Fixed Attenuator, SMA Male To SMA Female
Directional Aluminum Heatsink Black Anodized
Body Rated To 100 Watts Up To 1.5 GHz

TECHNICAL DATA SHEET

PE7022-40

**40 dB Fixed Attenuator, SMA Male To SMA Female Directional Aluminum Heatsink Black Anodized Body
Rated To 100 Watts Up To 1.5 GHz**

Configuration

Design	Fixed, Directional Attenuator
Connector 1	SMA Male
Connector 2	SMA Female
Body Material and Plating	Aluminum Heatsink, Black Anodized

Electrical Specifications

Frequency Range, GHz	DC to 1.5
Impedance, Ohms	50
Attenuation Value, dB	40
Maximum Input Power, Watts	100
Maximum VSWR	1.25:1

Frequency 1

Range, GHz	DC to 1.5
VSWR	1.25:1
Attenuation Accuracy, dB	± 1

Mechanical Specifications

Size

Length, in [mm]	5.655 [143.64]
Width, in [mm]	3.465 [88.01]
Height, in [mm]	3.465 [88.01]

Connector 1

Type	SMA Male
Hex Size, in.	5/16

Connector 2

Type	SMA Female
------	------------

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Fixed Attenuator, SMA Male To SMA Female Directional Aluminum Heatsink Black Anodized Body Rated To 100 Watts Up To 1.5 GHz PE7022-40](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



40 dB Fixed Attenuator, SMA Male To SMA Female
Directional Aluminum Heatsink Black Anodized
Body Rated To 100 Watts Up To 1.5 GHz

TECHNICAL DATA SHEET

PE7022-40

Plotted and Other Data

Notes:

Values at 25 °C, sea level

40 dB Fixed Attenuator, SMA Male To SMA Female Directional Aluminum Heatsink Black Anodized Body Rated To 100 Watts Up To 1.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Fixed Attenuator, SMA Male To SMA Female Directional Aluminum Heatsink Black Anodized Body Rated To 100 Watts Up To 1.5 GHz PE7022-40](http://www.pasternack.com/40db-fixed-sma-female-sma-male-100-watts-attenuator-pe7022-40-p.aspx)

URL: <http://www.pasternack.com/40db-fixed-sma-female-sma-male-100-watts-attenuator-pe7022-40-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE7022-40 CAD Drawing

40 dB Fixed Attenuator, SMA Male To SMA Female Directional Aluminum
Heatsink Black Anodized Body Rated To 100 Watts Up To 1.5 GHz

P/N	ATTEN.	FIGURE
PE7022-6	6 dB	1
PE7022-10	10 dB	1
PE7022-20	20 dB	1
PE7022-30	30 dB	1
PE7022-40	40 dB	1




FIGURE 1

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE7022

PASTERNACK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 022513

SCALE N/A

SIZE A

2231