



SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins

Electromechanical Relay Switches Technical Data Sheet

PE71S6487

Features

- Single Pole Six Throw (SP6T) Electromechanical Relay Switch
- DC to 26.5 GHz Frequency Range
- Normally Open Actuator
- 2M Lifecycle Rating
- Insertion Loss 0.4 dB typ
- Isolation > 70 dB typ
- VSWR as low as 1.25:1 max
- +28 Volt DC Bias
- Solder Terminal Pins for DC Control
- SMA Female Connectors
- -25°C to +65°C Operating Temperature
- Up to 20 Watt Average Power Handling
- 50 Ohm Design
- Hot Switching Capability - Consult Factory
- S-Parameter Data available upon request
- Rugged Design meets Mil-STD-202 Test Conditions

Applications

- Aerospace & Defense
- Test & Measurement
- Microwave Radio Systems
- Military & Commercial Communication Systems
- Research & Development
- SATCOM
- Wireless Communications
- Enterprise
- IoT

Description

The PE71S6487 is a Single Pole Six Throw (SP6T) electromechanical relay switch that operates across a wide frequency range from DC to 26.5 GHz and can handle up to 20 Watts of average power in a break before make condition. The 50 Ohm design is rated for 2M lifecycles and features a Normally Open Actuator where the selected position remains active with constant voltage, all positions are open when voltage is removed. Impressive typical performance includes 0.4 dB insertion loss and isolation greater than 70 dB. This switch requires +28Vdc bias voltage and operates over a temperature range of -25°C to +65°C. The rugged and compact package assembly supports SMA female connectors and solder terminal pins for DC control. And for highly reliable operation, the model is guaranteed to meet MIL-STD-202 environmental test conditions for shock and random vibration.

Electrical Specifications (TA = +25°C, DC Voltage = +28 Vdc)

Switch Type
Actuator Type

SP6T
Normally Open

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
Operating Voltage		+28		Volts
Actuating Set Current @ +28 Volts			140	mA
VSWR		1.3:1	1.8:1	
Insertion Loss		0.4	0.8	dB
Isolation	50	70		dB
Input Power (CW) (at 26.5 GHz)			20	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins PE71S6487](#)



SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6487

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 6	6 to 12	12 to 18	18 to 26.5		GHz
VSWR, Max	1.25:1	1.4:1	1.5:1	1.8:1		
Insertion Loss, Max	0.2	0.4	0.5	0.8		dB
Isolation, Min	70	60	60	50		dB

Mechanical Specifications

Size

Length	1.75 in [44.45 mm]
Width/Diameter	1.75 in [44.45 mm]
Height	1.75 in [44.45 mm]
Weight	0.1 lbs [45.36 g]

Connectors

RF Connector Type	SMA Female
-------------------	------------

Environmental Specifications

Temperature

Operating Range	-25 to +65 deg C
Storage Range	-55 to +100 deg C

Shock	MIL-STD-202 Method 213, Condition D, 500G (non oper)
-------	--

Vibration	MIL-STD-202 Method 204, Condition D, 10G RMS (non oper)
-----------	---

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins PE71S6487](#)




SP6T Electromechanical Relay Normally Open Switch, DC
to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6487

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins PE71S6487](#)



SP6T Electromechanical Relay Normally Open Switch, DC
to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6487



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins PE71S6487](#)




SP6T Electromechanical Relay Normally Open Switch, DC
to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins


Electromechanical Relay Switches Technical Data

PE71S6487

Power Handling vs. Frequency



Power Handling De-rating vs. Load VSWR



Power Handling Chart and Derating Curves based
on the following Test and Environmental Conditions:
Ambient temperature: 20-25°C
Altitude: Sea Level to 1,000 feet
Relative Humidity: 50-55%
Load VSWR: ≤ 1.20:1
Operation: Cold Switching

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins PE71S6487](#)



SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6487

SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins PE71S6487](https://www.pasternack.com/sp6t-electromechanical-relay-normally-open-switch-26.5-ghz-20w-28v-sma-pe71s6487-p.aspx)




URL: <https://www.pasternack.com/sp6t-electromechanical-relay-normally-open-switch-26.5-ghz-20w-28v-sma-pe71s6487-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE71S6487 CAD Drawing

SP6T Electromechanical Relay Normally Open Switch, DC to
26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	05/17/2022	T. GALLA



- NOTES:
- LABEL PER ILS-100-02. FOR INTERNAL REFERENCE ONLY.
LABEL LOCATION FOR REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ±.2	[5.08]	FRACTIONS
.XX = ±.02	[.51]	± 1/32
.XXX = ±.005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305]	±.1 [25] / -0
12 [305] < L ≤ 60 [1524]	±.2 [51] / -0
60 [1524] < L ≤ 120 [3048]	±.4 [102] / -0
120 [3048] < L ≤ 300 [7620]	±.6 [152] / -0
300 [7620] < L	±.5% / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

PE PASTERNAK
an INFINITE brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 2

SCALE N/A

REV A


ITEM NO. PE71S6487

DRAWN BY KGLEBOVA

CAGE CODE 53919

PE71S6487 CAD Drawing

SP6T Electromechanical Relay Normally Open Switch, DC to 26.5 GHz, 2M Lifecycles, 20W, 28V, SMA, Solder Pins



TRUTH TABLE/PIN ASSIGNMENT :
PIN ASSIGNMENT

TERMINALS PIN ASSIGNMENT	RF PATH					
	J1	J2	J3	J4	J5	J6
1	ON	OFF	OFF	OFF	OFF	OFF
2	OFF	ON	OFF	OFF	OFF	OFF
3	OFF	OFF	ON	OFF	OFF	OFF
4	OFF	OFF	OFF	ON	OFF	OFF
5	OFF	OFF	OFF	OFF	ON	OFF
6	OFF	OFF	OFF	OFF	OFF	ON

RF POSITION
SCHEMATIC

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:
X = ± 2 [.08] FRACTIONS
.XX = ± .02 [.51] ± 1/32
.XXX = ± .005 [.13] ANGLES ± 1°
CABLE LENGTH (L) TOLERANCES:
L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

 **PASTERNAK**
an INFINITI® brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE A CAGE CODE 53919 DRAWN BY KGLEBOVA ITEM NO. PE71S6487

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 2 OF 2
SCALE N/A

REV A