

SPDT Electromechanical Relay Latching Switch
DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts,
28V, Self Cut Off, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data Sheet

PE71S6492

Features

- Single Pole Double Throw (SPDT) Electromechanical Relay Switch
- DC to 12 GHz Frequency Range
- Latching Self Cut-Off Actuator
- Suppression Diodes
- 2M Lifecycle Rating
- Insertion Loss 0.4 dB typ
- Isolation > 90 dB typ
- VSWR as low as 1.25:1 max
- +28 Volt DC Bias
- Solder Terminal Pins for DC Control
- N Type Female Connectors
- -25°C to +65°C Operating Temperature
- Up to 160 Watt Average Power Handling
- 50 Ohm Design
- Hot Switching Capability - Consult Factory
- S-Parameter Data available upon request
- Rugged Design meets Mil-STD-202 Test Conditions

Applications

- Aerospace & Defense
- Test & Measurement
- Microwave Radio Systems
- Military & Commercial Communication Systems
- Research & Development
- SATCOM
- Wireless Communications
- Enterprise
- IoT

Description


The PE71S6492 is a Single Pole Double Throw (SPDT) electromechanical relay switch that operates across a wide frequency range From DC to 12 GHz and can handle up to 160W of average power in a break before make condition. The 50 Ohm design is rated for 2M lifecycles and features a Latching Self Cut-Off Actuator that magnetically latches in place after the control voltage is removed. For power sensitive applications, this is the best actuator option. An additional feature includes suppression diodes which limit voltage spikes or reverse current. Impressive typical performance includes 0.4 dB insertion loss and isolation greater than 90 dB. This switch requires +28Vdc bias voltage and operates over a temperature range of -25°C to +65°C. The rugged and compact package assembly supports N Type female connectors and solder terminal pins for DC control. And for highly reliable operation, the model is guaranteed to meet MIL-STD-202 environmental test conditions for shock and random vibration.

Electrical Specifications (TA = +25°C, DC Voltage = +28 Vdc)

Switch Type	SPDT
Actuator Type	Latching
Actuator Options	Self Cut Off

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
Operating Voltage		+28		Volts
Actuating Set Current @ +28 Volts			160	mA
VSWR		1.2:1	1.4:1	
Insertion Loss		0.2	0.5	dB
Isolation	60	90		dB
Input Power (CW) (at 12.4 GHz)			160	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins PE71S6492](#)



SPDT Electromechanical Relay Latching Switch
DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts,
28V, Self Cut Off, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6492

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 1	1 to 4	4 to 8	8 to 12		GHz
VSWR, Max	1.25:1	1.3:1	1.4:1	1.4:1		
Insertion Loss, Max	0.3	0.4	0.4	0.5		dB
Isolation, Min	90	80	70	60		dB

Mechanical Specifications

Size

Length	1.95 in [49.53 mm]
Width/Diameter	2.75 in [69.85 mm]
Height	0.92 in [23.37 mm]
Weight	0.1 lbs [45.36 g]

Connectors

RF Connector Type	N Female
-------------------	----------

Environmental Specifications

Temperature

Operating Range	-25 to +65 deg C
Storage Range	-55 to +100 deg C

Shock	MIL-STD-202 Method 213, Condition D, 500G (non oper)
-------	--

Vibration	MIL-STD-202 Method 204, Condition D, 10G RMS (non oper)
-----------	---

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins PE71S6492](#)




SPDT Electromechanical Relay Latching Switch
DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts,
28V, Self Cut Off, Diodes, Solder Pins


Electromechanical Relay Switches Technical Data

PE71S6492

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins PE71S6492](#)



SPDT Electromechanical Relay Latching Switch
DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts,
28V, Self Cut Off, Diodes, Solder Pins


Electromechanical Relay Switches Technical Data

PE71S6492



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins PE71S6492](#)


SPDT Electromechanical Relay Latching Switch
DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts,
28V, Self Cut Off, Diodes, Solder Pins




Electromechanical Relay Switches Technical Data

PE71S6492

Power Handling vs. Frequency



Power Handling De-rating vs. Load VSWR



Power Handling Chart and Derating Curves based on the following Test and Environmental Conditions:
Ambient temperature: 20-25°C
Altitude: Sea Level to 1,000 feet
Relative Humidity: 50-55%
Load VSWR: ≤ 1.20:1
Operation: Cold Switching

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins PE71S6492](#)



SPDT Electromechanical Relay Latching Switch
DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts,
28V, Self Cut Off, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6492

SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins PE71S6492](https://www.pasternack.com/spdt-electromechanical-relay-latching-switch-12.4-ghz-160w-28v-n-pe71s6492-p.aspx)

URL: <https://www.pasternack.com/spdt-electromechanical-relay-latching-switch-12.4-ghz-160w-28v-n-pe71s6492-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE71S6492 CAD Drawing

SPDT Electromechanical Relay Latching Switch DC to 12.4 GHz, 2M
Lifecycles, N, 160 Watts, 28V, Self Cut Off, Diodes, Solder Pins



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2	[.08]	FRACTIONS
.XX = ± .02	[.51]	± 1/32
.XXX = ± .005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12	[305]	= +1 [25] / -0
12 [305] < L ≤ 60	[1524]	= +2 [51] / -0
60 [1524] < L ≤ 120	[3048]	= +4 [102] / -0
120 [3048] < L ≤ 300	[7620]	= +6 [152] / -0
300 [7620] < L		= +5%L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

**PASTERNAK**
an INFINITE brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE	CAGE CODE	DRAWN BY	ITEM NO.
A	53919	KGLEBOVA	PE71S6492



THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET	2	OF	2
SCALE	N/A		
REV	A		

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE
WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.