

SPDT Electromechanical Relay Latching Switch,
DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V,
TTL, Diodes, Self Cut Off, N, Solder Pins

Electromechanical Relay Switches Technical Data Sheet

PE71S6493

Features

- Single Pole Double Throw (SPDT) Electromechanical Relay Switch
- DC to 12 GHz Frequency Range
- Latching Self Cut-Off Actuator
- TTL Logic Control
- Suppression Diodes
- 2M Lifecycle Rating
- Insertion Loss 0.2 dB typ
- Isolation > 90 dB typ
- VSWR as low as 1.25:1 max
- +12 Volt DC Bias
- Solder Terminal Pins for DC Command Control
- N Type Female Connectors
- -25°C to +65°C Operating Temperature
- Up to 160 Watt Average Power Handling
- 50 Ohm Design
- Hot Switching Capability - Consult Factory
- S-Parameter Data available upon request
- Rugged Design meets Mil-STD-202 Test Conditions

Applications

- Aerospace & Defense
- Test & Measurement
- Microwave Radio Systems
- Military & Commercial Communication Systems
- Research & Development
- SATCOM
- Wireless Communications
- Enterprise
- IoT

Description


The PE71S6493 is a Single Pole Double Throw (SPDT) electromechanical relay switch that operates across a wide frequency range from DC to 12 GHz and can handle up to 160 Watts of average power in a break before make condition. The 50 Ohm design is rated for 2 million lifecycles and features a Latching Self Cut-Off Actuator that magnetically latches in place after the control voltage is removed. For power sensitive applications, this is the best actuator option. Additional features include TTL control logic, and suppression diodes which limit voltage spikes or reverse current. Impressive typical performance includes 0.2 dB insertion loss and isolation greater than 90 dB. This switch requires +12Vdc bias voltage and operates over a temperature range of -25°C to +65°C. The rugged and compact package assembly supports N Type female connectors and Solder Pins for DC command control functions. And for highly reliable operation, the model is guaranteed to meet MIL-STD-202 environmental test conditions for shock and random vibration.

Electrical Specifications (TA = +25°C, DC Voltage = +12 Vdc)

Switch Type	SPDT
Actuator Type	Latching
Actuator Options	TTL Logic, Self Cut Off
TTL Control	on: 2.4 to 5.5 Volts off: 0 to 0.8 Volts

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
Operating Voltage		+12		Volts
Actuating Set Current @ +12 Volts			200	mA
VSWR		1.2:1	1.4:1	
Insertion Loss		0.2	0.5	dB

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins PE71S6493](#)



SPDT Electromechanical Relay Latching Switch,
DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V,
TTL, Diodes, Self Cut Off, N, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6493

Isolation	60	90		dB
Input Power (CW) (at 12.4 GHz)			160	Watts

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 1	1 to 4	4 to 8	8 to 12		GHz
VSWR, Max	1.25:1	1.3:1	1.4:1	1.4:1		
Insertion Loss, Max	0.3	0.4	0.4	0.5		dB
Isolation, Min	90	80	70	60		dB

Mechanical Specifications

Size

Length	1.95 in [49.53 mm]
Width/Diameter	2.75 in [69.85 mm]
Height	0.92 in [23.37 mm]
Weight	0.1 lbs [45.36 g]

Connectors

RF Connector Type	N Female
-------------------	----------

Environmental Specifications

Temperature

Operating Range	-25 to +65 deg C
Storage Range	-55 to +100 deg C

Shock	MIL-STD-202 Method 213, Condition D, 500G (non oper)
-------	--

Vibration	MIL-STD-202 Method 204, Condition D, 10G RMS (non oper)
-----------	---

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins PE71S6493](#)




SPDT Electromechanical Relay Latching Switch,
DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V,
TTL, Diodes, Self Cut Off, N, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6493

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins PE71S6493](#)



SPDT Electromechanical Relay Latching Switch,
DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V,
TTL, Diodes, Self Cut Off, N, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6493



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins PE71S6493](#)


SPDT Electromechanical Relay Latching Switch,
DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V,
TTL, Diodes, Self Cut Off, N, Solder Pins




Electromechanical Relay Switches Technical Data

PE71S6493

Power Handling vs. Frequency



Power Handling De-rating vs. Load VSWR



Power Handling Chart and Derating Curves based on the following Test and Environmental Conditions:
Ambient temperature: 20-25°C
Altitude: Sea Level to 1,000 feet
Relative Humidity: 50-55%
Load VSWR: ≤ 1.20:1
Operation: Cold Switching

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins PE71S6493](#)



SPDT Electromechanical Relay Latching Switch,
DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V,
TTL, Diodes, Self Cut Off, N, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6493

SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins PE71S6493](https://www.pasternack.com/spdt-electromechanical-relay-latching-switch-12.4-ghz-160w-12v-ttl-n-pe71s6493-p.aspx)

URL: <https://www.pasternack.com/spdt-electromechanical-relay-latching-switch-12.4-ghz-160w-12v-ttl-n-pe71s6493-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE71S6493 CAD Drawing

SPDT Electromechanical Relay Latching Switch, DC to 12.4 GHz, 2M lifecycles, 160 Watts, 12V, TTL, Diodes, Self Cut Off, N, Solder Pins



OPERATIONAL				
LOGIC TABLE				
TERMINALS	RF PORTS	INDICATOR		
1	2	J1	J2	A-C B-C
0	0	NO CHANGE		
0	1	OFF	ON	OFF ON
1	0	ON	OFF	ON OFF
1	1	FORBIDDEN		

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE IN INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2 [.08] FRACTIONS
.XX = ± .02 [.51] ± 1/32
.XXX = ± .005 [.13] ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.




PASTERNAK
an INFINITE brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE	CAGE CODE	DRAWN BY	ITEM NO.
A	53919	KGLEBOVA	PE71S6493

THIRD-ANGLE PROJECTION



THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET	2	OF	2
SCALE	N/A		
REV	A		