



Dual Junction Isolator with 40 dB Isolation from
2 GHz to 4 GHz, 50 Watts and SMA Female

Isolators Technical Data Sheet

PE83IR1017

Features

- Dual Junction Isolator
- Frequency Range of 2 to 4 GHz
- Female SMA Connectors
- Low VSWR

Applications

- Radar Systems
- Military
- Wireless Radio Systems
- Telecom Infrastructure
- Communication Systems
- R&D Labs
- Microwave Radio Systems

Description

The PE83IR1017 is a dual junction isolator offering 40 dB minimum of isolation over a frequency band of 2 to 4 GHz. This coaxial part uses SMA female connectors on all ports and has a power rating of 50 Watts in forward and 2 Watts in reverse direction.

Pasternack Enterprises offers a wide variety of isolators to fit your needs. These are two-port devices that transmit microwave or radio frequency power in one direction only and block the signal in the opposite direction. They can be thought of as a diode for RF energy. Isolators are used to isolate equipment from the effects of conditions outside of the equipment. For instance they are used to prevent a microwave source being detuned by a mismatched load. Pasternack's isolators feature excellent insertion loss, high isolation and reliability.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	2		4	GHz
Impedance		50		Ohms
Insertion Loss			1	dB
Isolation	40			dB
VSWR			1.3:1	
Forward Power, CW			50	Watts
Reverse Power, CW			2	Watts

Electrical Specification Notes:
Electrical Performance Is Guaranteed Only At 25C Ambient

Mechanical Specifications

Size	
Length	3.2 in [81.28 mm]
Width	0.6 in [15.24 mm]
Height	1.6 in [40.64 mm]
Weight	0.3545 lbs [160.8 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator with 40 dB Isolation from 2 GHz to 4 GHz, 50 Watts and SMA Female PE83IR1017](#)



Dual Junction Isolator with 40 dB Isolation from
2 GHz to 4 GHz, 50 Watts and SMA Female

Isolators Technical Data Sheet

PE83IR1017

Configuration

Design

Dual Junction

Package Style

Connectorized

Connector 1

SMA Female

Connector 2

SMA Female

Environmental Specifications

Temperature

Operating Range


0 to +50 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator with 40 dB Isolation from 2 GHz to 4 GHz, 50 Watts and SMA Female PE83IR1017](#)



Dual Junction Isolator with 40 dB Isolation from
2 GHz to 4 GHz, 50 Watts and SMA Female

Isolators Technical Data Sheet

PE83IR1017



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator with 40 dB Isolation from 2 GHz to 4 GHz, 50 Watts and SMA Female PE83IR1017](#)



Dual Junction Isolator with 40 dB Isolation from
2 GHz to 4 GHz, 50 Watts and SMA Female

Isolators Technical Data Sheet

PE83IR1017

Dual Junction Isolator with 40 dB Isolation from 2 GHz to 4 GHz, 50 Watts and SMA Female from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator with 40 dB Isolation from 2 GHz to 4 GHz, 50 Watts and SMA Female PE83IR1017](https://www.pasternack.com/dual-junction-isolator-40db-isolation-4-ghz-50-watts-sma-female-pe83ir1017-p.aspx)

URL: <https://www.pasternack.com/dual-junction-isolator-40db-isolation-4-ghz-50-watts-sma-female-pe83ir1017-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Dual Junction Isolator with 40 dB Isolation from 2 GHz to 4 GHz, 50 Watts and SMA Female

Technical drawing of the 2500 Series 100W Power Amplifier, showing front and side views with dimensions in inches and millimeters.

Front View Dimensions:


- Overall Width: 3.20 [81.3]
- Distance from Left Edge to Center of SMA Female Connector: 2.725 [69.22]
- Distance from Center of SMA Female Connector to Center of Label: 1.070 [27.18]
- Distance from Center of Label to Right Edge: 1.600 [40.64]
- Distance from Right Edge to Center of SMA Female Connector: 2.725 [69.22]
- Overall Height: 1.60 [40.6]
- Distance from Top Edge to Center of SMA Female Connector: 0.60 [15.2]
- Distance from Center of SMA Female Connector to Bottom Edge: 0.300 [7.62] TYP

Side View Dimensions:

- Overall Depth: 1.600 [40.64]
- Distance from Front Face to Center of SMA Female Connector: 0.800 [20.32]
- Distance from Center of SMA Female Connector to Back Face: 1.600 [40.64]

Labels and Callouts:

- 2X SMA FEMALE
- 4X #2-56 UNC-2B ∇ .180 [4.57] NEAR & FAR SIDE
- LABEL



PE83IR1017
2.00 - 4.00 GHz
DC WWWW

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

SCALE
N/A

Pasternack Enterprises, Inc.
P.O. Box 18759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE	CAGE CODE	DRAWN BY	ITEM NO.
------	-----------	----------	----------

PE83IR1017

REV	
-----	--

T-Rev.D