



SECTION A-A

DUST CAP AND LANYARD NOT SHOWN

RECOMMENDED PANEL OPENING

**NOTES:**

**MATERIAL:**

MAIN BODY AND DUST CAP: PBT + GF, UL94V-0

HOOD: MOLDED 25P PVC

**ADAPTER:**

BODY: COPPER, NICKEL PLATING

INSULATOR: WHITE PLASTIC STEEL

CONTACT: COPPER, GOLD PLATING

**PHYSICAL CHARACTERISTICS:**

OPERATING TEMPERATURE RANGE: -10°C TO +60°C.

STORAGE TEMPERATURE RANGE: -40°C TO +68°C.

HUMIDITY: 10% ~ 90% RH

IP RATING: IP68-WHEN DUST CAP IS ENGAGED.

**ELECTRICAL:**

IMPEDANCE: 75 OHM

**PACKAGING:**

ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS

**TOLERANCES:**

X = ± 2 [ 5.08 ] FRACTIONS ± 1/32  
 .XX = ± .02 [ .51 ]  
 .XXX = ± .005 [ .13 ] ANGLES ± 1°

**CABLE LENGTH (L) TOLERANCES:**

L ≤ 12 [305] = +1 [25] / -0  
 12 [305] < L ≤ 60 [1524] = +2 [51] / -0  
 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0  
 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0  
 300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.



Pasternack Enterprises, Inc.  
 P.O.Box 16759, Irvine, CA 92623.  
 Phone: 1.949.261.1920 | 1.866.727.8376  
 Fax: 1.949.261.7451  
 Website: www.pasternack.com  
 E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION



THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

SIZE A	CAGE CODE 53919	DRAWN BY DMA Y	ITEM NO. PEAD1266	REV A
-----------	--------------------	-------------------	----------------------	----------