



WR-42 Instrumentation Grade Waveguide E-Bend with UG-595/U Flange Operating from 18 GHz to 26.5 GHz

TECHNICAL DATA SHEET

PEW42B101

Pasternack's PEW42B101 is an E-Plane, 90 degree, WR-42 waveguide bend that operates from 18 GHz to 26.5 GHz. This waveguide bend offers a maximum VSWR of 1.10 and a typical insertion loss of 0.20 dB. The input of this waveguide section has a UG-595/U Flange. PEW42B101 is part of over 40,000 RF, microwave and millimeter wave components. Our instrumentation grade WR-42 waveguide bend will ship worldwide the same day it is purchased along with our other RF components.

- 90° Bend
- E-Plane
- WR-42 Waveguide
- UG-595/U Flange
- 18 GHz to 26.5 GHz Frequency Range
- Comprehensive waveguide offering also includes Straight Sections, H-Bends, Waveguide to Coax Adapters, Filters, Terminations, and more.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	18		26.5	GHz
VSWR			1.1:1	
Insertion Loss		0.2		dB

Mechanical Specifications

Waveguide Size Waveguide Design WR-42 Instrumentation Grade

Description	Flange 1	Waveguide	Flange 2
Flange Type	Square Cover		Square Cover
Flange Designation	UG-595/U	WR-42	UG-595/U
Material	Brass Copper	Brass Copper	Brass Copper
Plating	Gold	Gold	Gold

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-42 Instrumentation Grade Waveguide E-Bend with UG-595/U Flange Operating from 18 GHz to 26.5 GHz PEW42B101

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





WR-42 Instrumentation Grade Waveguide E-Bend with UG-595/U Flange Operating from 18 GHz to 26.5 GHz

TECHNICAL DATA SHEET

PEW42B101

WR-42 Instrumentation Grade Waveguide E-Bend with UG-595/U Flange Operating from 18 GHz to 26.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-42 Instrumentation Grade Waveguide E-Bend with UG-595/U Flange Operating from 18 GHz to 26.5 GHz PEW42B101

URL: https://www.pasternack.com/wr-42-waveguide-e-bend-ug-595-flange-18-26.5-ghz-pew42b101-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEW42B101 CAD Drawing

WR-42 Instrumentation Grade Waveguide E-Bend with UG-595/U Flange Operating from 18 GHz to 26.5 GHz

