



WR-28 Waveguide Electromechanical Relay SPDT
Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts,
UG-599/U Square Cover, 28V, Self Cut Off

Waveguide Electromechanical Relay Switches Technical

PEWGS6000

Features

- 26.5 to 40 GHz SPDT Waveguide Switch
- Optional DPDT Configuration
- WR-28 Waveguide with O-Rings
- Insertion Loss: 0.012 dB typ
- Isolation: 90 dB typ
- +28 Vdc Nominal Voltage
- Input Power Rating up to 0.55 kW CW max
- Latching Self Cut Off Actuator
- Position Indicator and Manual Override Access
- Fully Weatherized Package
- Quick Connect Circular DC Connector with Mate
- -40°C to +85°C Operating Temperature

Applications

- Electronic Warfare
- Electronic Countermeasures
- Microwave Radio
- VSAT
- Radar
- Space Systems
- Test Instrumentation
- Research and Development

Description

The PEWGS6000 electromechanical WR-28 waveguide switch operates across a wide frequency range from 26.5 GHz to 40 GHz and is configured for single pole double throw (SPDT) operation. A shorting plate on port 3 can be removed for optional double pole double throw (DPDT) operation. This innovative design features a latching Self Cut Off actuator and patented motor drive with arc suppression. The motor drive housing supports a viewable position indicator window and a cover that can be removed for manual override access.

Impressive performance includes 0.012 dB typ Insertion loss, 90 dB typ Isolation, 1.08:1 typ VSWR, and an operating life of 250K cycles minimum. The design operates across a temperature range of -40°C to +85°C, requires +28Vdc nominal bias voltage, and has an input power rating of up to 0.55 KW CW maximum. The waveguide ports have Grooved UG-599/U Square Cover Flanges (O-Rings included) for pressurized operation. The rugged package design is fully weatherized for up to 100% humidity exposure and supports a quick connect circular 6 pin MIL-SPEC DC bias connector with mate included.

Electrical Specifications

Switch Type	SPDT
Actuator Type	Latching
Switching Sequence	Break Before Make
Actuator Options	Self Cut Off, Window Indicator, Manual Override
Polarity	Negative Common

Description	Minimum	Typical	Maximum	Units
Frequency Range	26.5		40	GHz
Impedance		50		Ohms
Operating Voltage	21	28	32	Volts
Actuating Current @ 28 Volts		212	243	mA
VSWR		1.08:1	1.15:1	
Insertion Loss		0.012	0.15	dB
Isolation	55	90		dB
Switching Time		61	80	ms
Input Power (CW)			550	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off PEWGS6000](#)



WR-28 Waveguide Electromechanical Relay SPDT
Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts,
UG-599/U Square Cover, 28V, Self Cut Off

Waveguide Electromechanical Relay Switches Technical

PEWGS6000

Input Power (Peak) 10% Duty Cycle

13.3

KWatts

Mechanical Specifications

Size

Length	3.9 in [99.06 mm]
Width/Diameter	2.11 in [53.59 mm]
Height	2.11 in [53.59 mm]
Weight	1.005 lbs [455.86 g]

Operating Life (Cold Switching)

250,000 Cycles

Operating Pressure

30 psig

Configuration

Waveguide Size	WR-28
Flange Type	Square Cover
Flange Designation	UG-599/U
Body Material and Plating	Aluminum, Chem Film
Body Plating Specification	MIL-DTL-5541 Type II Class 3

Mechanical Specification Notes:

Production Burn-In IAW MIL-DTL-55041 1500 cycles

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-55 to +100 deg C

Ingress Protection (IP) Rating

IP67

Humidity

0-100%, Fully Weatherized

ESD Sensitivity

ESD Sensitive Material, Transport material in Approved ESD bags. Handle in approved ESD Workstation.



Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off PEWGS6000](#)




WR-28 Waveguide Electromechanical Relay SPDT
Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts,
UG-599/U Square Cover, 28V, Self Cut Off

Waveguide Electromechanical Relay Switches Technical

PEWGS6000

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off PEWGS6000](#)



WR-28 Waveguide Electromechanical Relay SPDT
Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts,
UG-599/U Square Cover, 28V, Self Cut Off

Waveguide Electromechanical Relay Switches Technical

PEWGS6000




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off PEWGS6000](#)



WR-28 Waveguide Electromechanical Relay SPDT
Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts,
UG-599/U Square Cover, 28V, Self Cut Off

Waveguide Electromechanical Relay Switches Technical

PEWGS6000



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off PEWGS6000](#)



**WR-28 Waveguide Electromechanical Relay SPDT
Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts,
UG-599/U Square Cover, 28V, Self Cut Off**

Waveguide Electromechanical Relay Switches Technical

PEWGS6000

WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band 40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off PEWGS6000](https://www.pasternack.com/wr-28-waveguide-electromechanical-relay-spd-t-latching-switch-40-ghz-pewgs6000-p.aspx)

URL: <https://www.pasternack.com/wr-28-waveguide-electromechanical-relay-spd-t-latching-switch-40-ghz-pewgs6000-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEWGS6000 CAD Drawing

WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band
40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off



DWG TITLE

PEWGS6000

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

PE PASTERNAK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAGE CODE 53919

CAD FILE 122216




SCALE N/A

SIZE A



2233

PEWGS6000 CAD Drawing

WR-28 Waveguide Electromechanical Relay SPDT Latching Switch, Ka Band
40 GHz Max. Freq., 550 Watts, UG-599/U Square Cover, 28V, Self Cut Off



View A



DWG TITLE

PEWGS6000

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAGE CODE 53919

CAD FILE 122216

SCALE N/A

SIZE A

2233