



WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V

Waveguide Electromechanical Relay Switches Technical

PEWGS6070

Features

- 7.05 to 10 GHz SPDT Waveguide Switch
- Optional DPDT Configuration
- WR112 Waveguide with CPR Flat Flanges
- Failsafe Actuator and Position Indicator
- Insertion Loss: 0.04 dB typ
- Isolation: 88 dB typ
- Switching Time: <125 msec typ
- +12 Vdc Nominal Voltage
- Input Power Rating up to 7 kW CW max
- Unpressurized Peak Power Rating up to 202 kW
- Manual Override Access
- Fully Weatherized Package
- Quick Connect Circular DC Connector with Mate
- -40°C to +85°C Operating Temperature

Applications

- Electronic Warfare
- Electronic Countermeasures
- Microwave Radio
- VSAT
- Radar
- Space Systems
- Test Instrumentation
- Research and Development

Description

The PEWG6070 WR112 waveguide electromechanical switch operates across a wide frequency range from 7.05 to 10 GHz and is configured for single pole double throw (SPDT) operation. A shorting plate on port 3 can be removed for optional double pole double throw (DPDT) operation. This innovative design features a failsafe actuator with TTL logic control, and a patented motor drive with arc suppression. The motor drive housing supports a viewable position indicator window and a cover that can be removed for manual override access. Impressive typical performance includes 0.04 dB insertion loss, 88 dB Isolation and 1.07:1 VSWR. The design operates across a temperature range of -40°C to +85°C, requires +12Vdc nominal bias voltage, and has an input power rating of up to 7 kW CW maximum, and an unpressurized peak power rating up to 202 kW. Operating life of 250K cycles minimum. The waveguide ports have CPR Flat flanges. The rugged package design is fully weatherized for up to 100% humidity exposure and supports a quick connect circular 6 pin MIL-SPEC DC bias connector with mate included.

Electrical Specifications

Switch Type	SPDT/DPDT
Actuator Type	Failsafe
Actuator Options	TTL Logic, Window Indicator, Manual Override
TTL Control	on: 2.4 to 5.5 Volts
	off: 0 to 0.8 Volts
	5 mA at 5.5 Volts
	5 mA at 0.8 Volts
TTL Control Current	

Description	Minimum	Typical	Maximum	Units
Frequency Range	7.05		10	GHz
Impedance		50		Ohms
Operating Voltage	10.8	12	13.2	Volts
Actuating Current @ 12 Volts		245	300	mA
VSWR		1.07:1	1.1:1	
Insertion Loss		0.04	0.05	dB
Isolation	80	88		dB
Switching Time		<125		ms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V PEWGS6070](#)



WR112 SPDT/DPDT Failsafe, X Band Waveguide
Electromechanical Relay Switch, 7.05 GHz
to 10 GHz, 7 kW CPR-Flat, TTL, 12V

Waveguide Electromechanical Relay Switches Technical

PEWGS6070

Input Power (CW)	7	kWatts
Input Power (Peak/Unpressurized)	202	kWatts

Electrical Specification Notes:

Active logic switch command duration must be maintained to keep switch in energized position.

Maximum switching rate not to exceed 30 per minute

Mechanical Specifications

Size

Length	2.25 in [57.15 mm]
Width/Diameter	2.43 in [61.72 mm]
Height	4.85 in [123.19 mm]
Weight	1.45 lbs [657.71 g]

Operating Life

250,000 Cycles

Operating Pressure

30 psig

Configuration

Waveguide Size

WR-112

Flange Type

CPR Flat

Body Material and Plating

Aluminum, Black

Body Plating Specification

MIL-DTL-5541

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Storage Range

-55 to +100 deg C

Humidity

0 to 100% Fully Weatherized IAW IP67

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V PEWGS6070](#)




WR112 SPDT/DPDT Failsafe, X Band Waveguide
Electromechanical Relay Switch, 7.05 GHz
to 10 GHz, 7 kW CPR-Flat, TTL, 12V

Waveguide Electromechanical Relay Switches Technical


PEWGS6070

Typical Performance Data

Typical (Position 1) Insertion Loss



Typical (Position 2) Insertion Loss



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V PEWGS6070](#)




WR112 SPDT/DPDT Failsafe, X Band Waveguide
Electromechanical Relay Switch, 7.05 GHz
to 10 GHz, 7 kW CPR-Flat, TTL, 12V


Waveguide Electromechanical Relay Switches Technical

PEWGS6070

**Typical (Position 1)
VSWR**



**Typical (Position 2)
VSWR**



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V PEWGS6070](#)




WR112 SPDT/DPDT Failsafe, X Band Waveguide
Electromechanical Relay Switch, 7.05 GHz
to 10 GHz, 7 kW CPR-Flat, TTL, 12V


Waveguide Electromechanical Relay Switches Technical

PEWGS6070

Typical (Position 1) Isolation



Typical (Position 2) Isolation



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V PEWGS6070](#)



WR112 SPDT/DPDT Failsafe, X Band Waveguide
Electromechanical Relay Switch, 7.05 GHz
to 10 GHz, 7 kW CPR-Flat, TTL, 12V

Waveguide Electromechanical Relay Switches Technical

PEWGS6070

WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V PEWGS6070](https://www.pasternack.com/wr-112-waveguide-electromechanical-relay-spdt-dpdt-failsafe-switch-10-ghz-7kw-cpr-flat-ttl-12v-pewgs6070)




URL: <https://www.pasternack.com/wr-112-waveguide-electromechanical-relay-spdt-dpdt-failsafe-switch-10-ghz-7kw-cpr-flat-ttl-12v-pewgs6070-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEWGS6070 CAD Drawing

WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical
Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	03/26/2021	TGALLA



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:


X = +.2 [5.08] FRACTIONS
XX = +.02 [.51] +.132
XXX = ±.005 [.13] ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:
L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5% / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.



Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com



THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 2

SCALE N/A



SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	53919	DFRISIELLO	PEWGS6070	A

- NOTES:
1. LABEL PER ILS-100-02. FOR INTERNAL REFERENCE ONLY.
 2. SERIAL NUMBER AND DATE CODE ARE COMBINED. EX: 2020040500001

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE
WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

PEWGS6070 CAD Drawing

WR112 SPDT/DPDT Failsafe, X Band Waveguide Electromechanical
Relay Switch, 7.05 GHz to 10 GHz, 7 kW CPR-Flat, TTL, 12V



View A

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE IN INCHES
DIMENSIONS IN [] ARE IN MILLIMETERS

TOLERANCES:

FRACTIONS
X = +.2 [5.08]
XX = +.02 [.51]
XXX = +.005 [.13]

ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:
L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +9% L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

PASTERNAK
an INFINITI® brand

Pastermack Enterprises, Inc.
P. O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pastermack.com
E-mail: sales@pastermack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.
SHEET 2 OF 2
SCALE N/A
REV A

SIZE A

CAGE CODE 53919

DRAWN BY DFRISIELLO

ITEM NO. PEWGS6070